

# PRODUCT DATASHEET

## ST CLAS A 40 4 W/2700K E27

LED Retrofit CLASSIC A | LED lamps, classic bulb shape



---

### AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)
- Perfect for decorative installations

---

### PRODUCT BENEFITS

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Correct operation even at low temperatures

---

### PRODUCT FEATURES

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps
- Lifetime: up to 15,000 h



- Beam angle: up to 300°

**TECHNICAL DATA**

Electrical data

|  |             |
|--|-------------|
| Rated wattage                            | 4.00 W      |
| Nominal wattage                          | 4.00 W      |
| Nominal voltage                          | 220...240 V |
| Max. lamp no. on circuit break. 10 A (B) | 156         |
| Max. lamp no. on circuit break. 16 A (B) | 250         |
| Operating frequency                      | 50...60 Hz  |
| Power factor $\lambda$                   | > 0.40      |
| Claimed equiv. conventional lamp power   | 40 W        |


Photometrical data

|   |                     |
|---|---------------------|
| Nominal luminous flux                   | 470 lm              |
| Rated luminous flux                     | 470 lm              |
| Lumen main.fact.at end of nom.life time | 0.70                |
| Light color (designation)               | Warm White          |
| Color temperature                       | 2700 K              |
| Luminous flux                           | 470 lm              |
| Color rendering index Ra                | ≥80                 |
| Standard deviation of color matching    | ≤6 sdc <sub>m</sub> |
| Rated color temperature                 | 2700 K              |

Light technical data

|                     |          |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

Dimensions & weight



|                |          |
|----------------|----------|
| Overall length | 105.0 mm |
|----------------|----------|

|                   |          |
|-------------------|----------|
| <b>Diameter</b>   | 60.0 mm  |
| <b>Outer bulb</b> | A60      |
| <b>Length</b>     | 105.0 mm |

#### Temperatures & operating conditions

|   |              |
|---|--------------|
| <b>Ambient temperature range</b>            | -20...+40 °C |
| <b>Maximum temperature at tc test point</b> | 50 °C        |

#### Lifespan

|   |         |
|---|---------|
| <b>Nominal lamp life time</b>                   | 15000 h |
| <b>Rated lamp life time</b>                     | 15000 h |
| <b>Number of switching cycles</b>               | 100000  |
| <b>Lumen maintenance at end of service life</b> | 0.70    |

#### Additional product data

|                                    |  |
|------------------------------------|--|
| <b>Base (standard designation)</b> | E27  |
| <b>Mercury content</b>             | 0.0 mg   |
| <b>Mercury-free</b>                | Yes  |
| <b>Show WEEE picto</b>             | Yes  |
| <b>Product remark</b>              | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

#### Capabilities

|                 |    |
|-----------------|----|
| <b>Dimmable</b> | No |
|-----------------|----|

#### Certificates & standards

|                                |             |
|--------------------------------|-------------|
| <b>Energy efficiency class</b> | A++         |
| <b>Energy consumption</b>      | 4 kWh/1000h |

#### Country-specific categorizations

|                        |                 |
|------------------------|-----------------|
| <b>Order reference</b> | LEDSCLA40 4W/82 |
|------------------------|-----------------|

#### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075112216 | Folding carton box<br>1      | 60 mm x 60 mm x 111 mm               | 42.00 g      | 0.40 dm <sup>3</sup> |
| 4058075112223 | Shipping carton box<br>10    | 322 mm x 134 mm x 120 mm             | 583.00 g     | 5.18 dm <sup>3</sup> |

|               |                           |                          |          |                      |
|---------------|---------------------------|--------------------------|----------|----------------------|
| 4058075330214 | Folding carton box<br>2   | 61 mm x 116 mm x 111 mm  | 98.00 g  | 0.79 dm <sup>3</sup> |
| 4058075330221 | Shipping carton box<br>10 | 324 mm x 128 mm x 121 mm | 596.00 g | 5.02 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.