

PRODUCT DATASHEET SMART+ Wifi Planon Plus 300x300mm RGB + White

SMART+ Planon Plus RGBW | Panel luminaires with WiFi technology



Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Easy and quick installation

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi



TECHNICAL DATA

Electrical data


Nominal wattage	20.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	200 mA
Max. number of luminaires per miniature circuit breaker B16	8
Max. number of luminaires per miniature circuit breaker C16	12
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	1400 lm	
Total luminous flux of contained light sources	2300 lm	
Luminous efficacy	70 lm/W	
Color temperature	3000 K	
Light color (designation)	RGBW	
Color rendering index Ra	≥80	
Standard deviation of color matching	< 6 sdcm	
Flickering metric (Pst LM)	≤1	
Stroboscope effect metric (SVM)	≤0.4	
Photobiological safety group acc. to EN62778	RG0	
Photobiological safety group acc. to EN62471	RG0	
Beam angle	110°	

Dimensions & Weight

Length	300.00 mm
Width	300.00 mm
Height	56.00 mm
Product weight	1150.00 g



SMART WIFI PLANON PLUS 30X30 RGBW WT

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	PMMA
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+70 °C	
Type of connection	Terminal, 2-Pole (L, N)	
Type of protection	IP20	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Ceiling	
Application environment	Indoor	
With light source	No	

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	15000

Certificates & Standards

Standards	CE / EAC / UKCA

Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
--

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	SMART+ PLANON PLUS
PDF	Declarations of conformity	SMART WIFI PLANON PLUS 30X30 RGBW LEDV
PDF	Declarations of conformity UKCA	SMART WIFI AND SUNATHOME
PDF	EU Data Act	SMART WiFi Lamps and Luminaires

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075495708	Folding box 1	332 mm x 82 mm x 334 mm	1396.00 g	9.09 dm ³
4058075495715	Shipping box 5	427 mm x 347 mm x 358 mm	7925.00 g	53.04 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/en-int/home-lighting/services/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.