

PRODUCT DATASHEET DL IP44 FRAME DN 115 WT

DOWNLIGHT IP44 FRAME | Surface mounting frame for Downlight IP44



Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Shops
- Bathrooms

Product benefits

- Easily installed

Product features


- Robust polycarbonate casing
- Mounting accessories included




TECHNICAL DATA

Dimensions & Weight

Diameter	115 mm
Height	47 mm
Product weight	65.00 g





Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)

Application & Mounting

Mounting type	Surface
Mounting location	Ceiling
Replaceable light source	No

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	DL IP44 FRAME DN WT

	Documents and certificates	Document name	
POF	User instruction / safety instructions	DL IP44 FRAME DN BK/WT	
POF	Legal information	DL IP44 DN 115 8W 830 WT	
POF	Legal information	DL IP44 DN WT	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
POF	Declarations of conformity	DL IP44 FRAME DN	
PDF	Declarations of conformity UKCA	UKCA Declaration of Conformity DOWNLIGHT IP44 DN WT	
	Tender texts Do	cument name	

Tender documents

LOGISTICAL DATA


ر ∰

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075709904	Folding box 1	120 mm x 53 mm x 124 mm	92.00 g	0.79 dm ³
4058075709911	Shipping box 10	279 mm x 250 mm x 140 mm	1099.00 g	9.77 dm ³

DOWNLIGHT IP44 FRAME DN 115 WT-EN

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.