


# PRODUCT DATASHEET

## SL AREA SPD SM V 30W 765 RV20ST GY

STREETLIGHT AREA SMALL RV20ST | Fitting a broad range of street and area lighting applications



### Areas of application

- Outdoor use (IP66)
- M-, C- and P-class roads acc. to EN 13201
- Car parks
- Area lighting

### Product benefits

- Functional and minimalistic design
- Low maintenance and operation costs due to long lifetime of LED
- 5 years guarantee

### Product features

- Light distributions optimized for streets of similar width to the pole height
- Spigot included, suitable for 48...60 mm diameter poles
- Adjustable spigot for both side-entry and post-top installation
- +/- 30° tilt angle adjustment without opening the housing
- High luminous efficacy: up to 135 lm/W
- Operating temperature: -30...50 °C
- High surge protection: up to 10 kV (L/N-PE)




---

**TECHNICAL DATA****Electrical data**

|                                                             |                       |
|-------------------------------------------------------------|-----------------------|
| Nominal wattage                                             | 30.00 W               |
| Nominal voltage                                             | 100...240 V           |
| Mains frequency                                             | 50...60 Hz            |
| Nominal current                                             | 135.000 mA            |
| Inrush current                                              | 8.9 A                 |
| Inrush current time $T_{h50}$                               | 100 $\mu$ s           |
| Max. number of luminaires per miniature circuit breaker B16 | 88                    |
| Max. number of luminaires per miniature circuit breaker C10 | 55                    |
| Max. number of luminaires per miniature circuit breaker C16 | 40                    |
| Power factor $\lambda$                                      | > 0.90                |
| Total harmonic distortion                                   | < 20 %                |
| Protection class                                            | I                     |
| Surge capability (L-N)                                      | 10 kV                 |
| Surge capability (L/N-Ground)                               | 10 kV                 |
| Operating mode                                              | Integrated LED driver |

**Photometrical data**


|                                              |                      |
|----------------------------------------------|----------------------|
| Luminous flux                                | 4050 lm              |
| Luminous efficacy                            | 135 lm/W             |
| Color temperature                            | 6500 K               |
| Light color (designation)                    | Cool Daylight        |
| Color rendering index Ra                     | 70                   |
| Standard deviation of color matching         | < 5 sdc <sub>m</sub> |
| Low flicker                                  | Yes                  |
| Photobiological safety group acc. to EN62778 | RG1                  |
| Photobiological safety group acc. to EN62471 | RG1                  |
| Beam angle                                   | 58° x 160°           |



SL AREA 30W

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 448.00 mm |
| Width          | 172.00 mm |
| Height         | 73.00 mm  |
| Product weight | 1450.00 g |
| Cable length   | 500 mm    |



SL AREA 30W

Materials & Colors

|                                            |                    |
|--------------------------------------------|--------------------|
| Product color                              | Gray               |
| Housing color                              | Gray               |
| Body material                              | Aluminum           |
| Cover material                             | Polycarbonate (PC) |
| Light emitting surface material            | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |

Application & Mounting

|                                        |                     |
|----------------------------------------|---------------------|
| Ambient temperature range              | -30...+50 °C        |
| Temperature range at storage           | -30...+80 °C        |
| Type of connection                     | Cable, 3-pole       |
| Type of protection                     | IP66                |
| Protection class IK (shock resistance) | IK08                |
| Dimmable                               | No                  |
| Mounting type                          | Side entry post top |
| Mounting location                      | Pole                |
| Application environment                | Outdoor             |
| Adjustable                             | Yes                 |
| With light source                      | Yes                 |
| Replaceable light source               | No                  |

### Lifespan

|                            |                        |
|----------------------------|------------------------|
| Lifespan L70/B50 at 25 °C  | 100000 h <sup>1)</sup> |
| Lifespan L80/B10 at 25 °C  | 88000 h <sup>1)</sup>  |
| Lifespan L80/B50 at 25 °C  | 88000 h                |
| Lifespan L90/B10 at 25 °C  | 44000 h                |
| Number of switching cycles | 100000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Control gear

|                             |        |
|-----------------------------|--------|
| Output current              | 160 mA |
| ECG - Output ripple current | < 5 %  |

### Sensor

|                                                    |       |
|----------------------------------------------------|-------|
| Type of connection for sensor/communication module | Other |
|----------------------------------------------------|-------|

### Certificates & Standards

|                                                      |                          |
|------------------------------------------------------|--------------------------|
| Standards                                            | CE / REACH / RoHS / ENEC |
| Luminaire with limited surface temperature, "D sign" | No                       |
| Ball shot safe                                       | No                       |

### DOWNLOAD DATA

| Documents and certificates                                                       |                                        | Document name                      |
|----------------------------------------------------------------------------------|----------------------------------------|------------------------------------|
|  | User instruction / safety instructions | UI SL AREA V                       |
|  | Legal information                      | Legal Insert SL AREA SPD           |
|  | Legal information                      | SL AREA                            |
|  | Legal information                      | Informationstext 18 Abs 4 ElektroG |
|  | Declarations of conformity             | CE Declaration SL AREA             |
|  | Declarations of conformity UKCA        | UKCA Declaration SL AREA           |
|  | Certificates                           | ENEC Certificate SL AREA           |

| Photometric and lighting design files                                              |                                     | Document name                   |
|------------------------------------------------------------------------------------|-------------------------------------|---------------------------------|
|   | IES file (IES)                      | SL AREA SPD SMV 30W765 RV20STGY |
|  | LDT file (Eulumdat)                 | SL AREA SPD SMV 30W765 RV20STGY |
|  | ULD file (DIALux)                   | SL AREA SPD SMV 30W 765         |
|  | ROLF file (RELUX)                   | SL AREA SPD SMV 30W765 RV20STGY |
|  | Light distribution curve type polar | SL AREA 30W                     |

| Tender texts                                                                       | Document name                                                          |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------|
|  | Tender documents<br>STREETLIGHT AREA SMALL RV20ST 30W 765 RV20ST GY-EN |


LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854030338 | Folding box<br>1             | 368 mm x 117 mm x 170 mm             | 1789.00 g    | 7.32 dm <sup>3</sup>  |
| 4099854030345 | Shipping box<br>4            | 493 mm x 211 mm x 347 mm             | 7156.00 g    | 36.10 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### ADDITIONAL CATALOG INFORMATION



#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.