

PRODUCT DATASHEET HID LED HIGHBAY UNIVERSAL PERFORMANCE 21000 LM 150W 840 E40

HID LED HIGHBAY UNIVERSAL PERFORMANCE | LED replacement for HID lamps for high-bay luminaires



Areas of application

- LED alternative for applications requiring a high luminous flux
- Industrial and storage facilities
- Outdoor applications only in suitable luminaires

Product benefits

- Direct replacement for traditional HID lamps thanks to CCG and ignitor compatibility
- Operation on AC mains for highest energy efficiency possible
- Energy savings of up to 68 % when replacing traditional HQI lamps
- Effective thermal management for wide operating temperature range
- Low maintenance costs thanks to long lifetime
- Instant 100 % light, no warm-up time

Product features

- Type of protection: IP40
- High surge protection: up to 4 kV (L-N)





TECHNICAL DATA


Electrical data

Nominal wattage	150 W
Construction wattage	150.00 W
Nominal voltage	220240 V
Operating mode	CCG, AC Mains, ignitor
Claimed equiv. conventional lamp power	400 W
Nominal current	700 mA
Type of current	AC
Inrush current	5.84 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	8
Max. lamp number on MCB B10 A - CCG without compensation	7
Max. lamp number on MCB B10 A - CCG with compensation	6
Max. lamp number on MCB B16 A	15
Max. lamp number on MCB B16 A - CCG without compensation	11
Max. lamp number on MCB B16 A - CCG with compensation	10
Total harmonic distortion	20 %
Power factor λ	> 0.90
Surge capability (L-N)	4 kV

Photometrical data

Luminous intensity	9402 cd
Luminous flux	21000 lm
Nominal useful luminous flux 90°	21000 lm
Luminous efficacy	140 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	9402 cd
Rated LLMF at 6,000 h	0.80

Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0,4



EPREL data spectral diagram PROF LEDr 4000K

Light technical data

Beam angle	100 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	263.00 mm
Diameter	250.00 mm
Product weight	1380.00 g

Temperatures & operating conditions

Ambient temperature range	-40+50 °C ¹⁾
Maximum temperature at tc test point	90 °C

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70

Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	E40
Mercury content	0.0 mg
Mercury-free	Yes
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	D 1)
Energy consumption	150.00 kWh/1000h
Type of protection	IP40
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG1
Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local country-specific categorizations)	owest efficiency)
	owest efficiency) HID LED HB UN P
Country-specific categorizations	
Country-specific categorizations Order reference	
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage	HID LED HB UN P
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage	HID LED HB UN P
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015	HID LED HB UN P -40+80 °C
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used	HID LED HB UN P -40+80 °C LED
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional	HID LED HB UN P -40+80 °C LED DLS
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains	HID LED HB UN P -40+80 °C LED DLS MLS
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface)	HID LED HB UN P -40+80 °C LED DLS MLS E40
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	HID LED HB UN P -40+80 °C LED DLS MLS E40 No
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source	HID LED HB UN P -40+80 °C LED DLS MLS E40 No No
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope	HID LED HB UN P -40+80 °C LED DLS MLS E40 No No No
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source	HID LED HB UN P -40+80 °C LED DLS MLS E40 No No No No
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source Anti-glare shield	HID LED HB UN P -40+80 °C LED DLS MLS E40 No No No No No

No

Claim of equivalent power

Length	263.00 mm
Height	250.00 mm
Width	250.00 mm
Chromaticity coordinate x	0.382
Chromaticity coordinate y	0.38
R9 Colour rendering index	1
Beam angle correspondence	WIDE_CONE_120
Survival factor	0,90
Displacement factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	1160650
Model number	AC41485,AC41485

EQUIPMENT / ACCESSORIES

- Safety sling for lamp included

Safety advice

- The bulb may be larger and heavier than the replaced bulb. Before installation it must be checked, if the luminaire and especially the holder is capable of carrying the weight of the lamp. Safety sling has to be installed.
- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.
- $-\,$ Only suitable for temperatures of up to 50 $^{\circ}\text{C}$ inside of the luminaire.
- Not suitable for operation with electronic control gear.
- All electrical connections must be made by a qualified person.

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User instruction / safety instructions	HID LED HIGHBAY UNIVERSAL	
POF	Legal information	Informationstext 18 Abs 4 ElektroG	
Declarations of conformity CE Declaration HID LED HB UN Ledvance		CE Declaration HID LED HB UN Ledvance	
Declarations of conformity UKCA		HID LED HIGHBAY UN	

Photometric and lighting design	gn files	Document name	
IES file (IES)		HID LED HB 150W-840 230VUN E40	
LDT file (Eulumdat)		HID LED HB 150W 840 230VUN E40	
UGR file (UGR table)		HID LED HB 150W-840 230VUN E40	
Light distribution curve type c	one	HID LED HB 150W-840 230VUN E40	
Light distribution curve type p	olar	HID LED HB 150W-840 230VUN E40	
Spectral power distribution		EPREL data spectral diagram PROF LEDr 4000K	
Tender texts	Document name		
Tender documents	HID LED Highbay (Universal P 21000 LM 150W 840 E40-en	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075780408	Folding box 1	255 mm x 255 mm x 320 mm	1700.00 g	20.81 dm ³
4058075780415	Shipping box 4	530 mm x 530 mm x 348 mm	8474.00 g	97.75 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.