

PRODUCT DATASHEET

PL CMFT 1200 P 33W 830 U19 PS

PANEL COMFORT 1200 UGR<19 PS | Rectangular recessed panel luminaires with power select (PS) feature and low glare, for 1200 x 300 mm ceiling systems



Areas of application

- Direct replacement for recessed luminaires with fluorescent lamps
- Offices, conference rooms
- Reception areas, foyers, corridors, elevators
- Suitable for recessed ceiling systems with grid size of 1200 x 300 mm

Product benefits

- Highly versatile due to selectable power steps (Power Select - PS) on the driver
- Tool-free electrical connection due to push button connector
- Through-wiring possible with included connector box
- Energy savings thanks to high system efficacy: up to 130 lm/W
- Good glare reduction (UGR < 19)
- High color consistency with SDCM 3
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- External driver for extended flexibility and easy installation
- Low flicker light thanks to special electronic control gear
- Emergency lighting possible with LEDVANCE Emergency Conversion Box
- 5 years guarantee

Product features

- Extruded aluminum frame



- Polystyrene diffuser
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Luminaire versions available with on-off or IoT-ready DALI-2 driver
- Lifetime (L80/B10): 70,000 h (at 25 °C)

TECHNICAL DATA

Electrical data


Nominal wattage	33 W / 28 W / 24 W ¹⁾
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	150.000 mA
Inrush current	9 A
Inrush current time T _{h50}	690 µs
Max. number of luminaires per miniature circuit breaker B16	14
Max. number of luminaires per miniature circuit breaker C10	15
Max. number of luminaires per miniature circuit breaker C16	24
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	II
Operating mode	External LED driver

¹⁾ For possible options refer to lumen/power table image / CRI80 versions of the Panel Comfort family are fulfilling the technical minimum requirements according to the German BEG subsidy program for energy efficient luminaires


Photometrical data

Luminous flux	4320 lm / 3640 lm / 3120 lm ¹⁾
Luminous efficacy	130 lm/W ¹⁾
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	≤3 sdc _m
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	90 °
UGR	< 19


¹⁾ For possible options refer to lumen/power table image / CRI80 versions of the Panel Comfort family are fulfilling the technical minimum requirements according to the German BEG subsidy program for energy efficient luminaires




PL CMFT 1200 24W 830 U19 PS




PL CMFT 1200 33W 830 U19 PS




PL CMFT 1200 33W 830 U19 PS
EM CONVERSION BOX




PL CMFT 1200 28W 830 U19 PS




PL CMFT 1200 24W 830 U19 PS



PL CMFT 1200 33W 830 U19 PS




PL CMFT 1200 33W 830 U19 PS
EM CONVERSION BOX



PL CMFT 1200 28W 830 U19 PS

Dimensions & Weight

Length	1195.00 mm
Width	295.00 mm
Height	11.00 mm
Product weight	2940.00 g



PL COMP 1200

Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Cover material	Polystyrene (PS)
Light emitting surface material	Polystyrene
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP40/IP20
Protection class IK (shock resistance)	IK02
Dimmable	No
Mounting type	Recessed/Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Mounting length	1185 mm
Mounting width	285 mm
Mounting depth	50,0 mm
Adjustable	No
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	70000 h ¹⁾
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	48000 h
Number of switching cycles	50000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	750 mA
ECG - Output ripple current	< 5 %
ECG - Length	143 mm
ECG - Width	49 mm
ECG - Height	30 mm
Recommended control gear	OSRAM OTI DALI 50/220-240/1A4 NFC; Tridonic LCA 45W 500-1400mA one4all SC PRE

Emergency lighting

Type of Emergency Lighting (EL)	Optional EL unit (battery and controller) for decentral operation available separately
---------------------------------	--

Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00012-V01.01-EN
Replaceable light source (EPREL)	Not replaceable

Additional product data

Added function	MULTI SELECT
----------------	--------------

Accessories Optional

Product image	Product name	EAN
	PANEL 1200 CABLE EXT TWIST LOCK	4099854018510
	EM CONVERSION BOX	4058075237025
	PANEL 1200x300 RECESSED MOUNT FRAME	4058075472976

Product image	Product name	EAN
	PANEL 1200 Surface Mount Kit	4058075108820
	PANEL RECESSED MOUNT CLIPS VAL 4x	4058075409859
	PANEL Suspension Kit	4058075402928
	PANEL 1200 X 300 SF MOUNT KIT H70 VAL	4099854018497

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The luminaires are not suitable for covering with thermally insulated material.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	PL CMFT 1200 P
	Legal information	LISO Insert Panel CMFT 1200 P
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	EM Insert PL COMFORT
	Declarations of conformity	CE Declaration PL CMFT 1200 PS
	Declarations of conformity UKCA	UKCA Declaration PL CMFT PS


Photometric and lighting design files		Document name
	IES file (IES)	PL CMFT 1200 33W 830 U19 PS
	LDT file (Eulumdat)	PL CMFT 1200 33W 830 U19 PS
	ULD file (DIALux)	PL CMFT 1200 P 33W 830 U19
	ROLF file (RELUX)	PL CMFT 1200 P 33W 830
	UGR file (UGR table)	PL CMFT 1200 24W 830 U19 PS
	UGR file (UGR table)	PL CMFT 1200 28W 830 U19 PS
	UGR file (UGR table)	PL CMFT 1200 33W 830 U19 PS EM CONVERSION BOX
	UGR file (UGR table)	PL CMFT 1200 33W 830 U19 PS
	Light distribution curve type cone	PL CMFT 1200 24W 830 U19 PS
	Light distribution curve type cone	PL CMFT 1200 28W 830 U19 PS
	Light distribution curve type cone	PL CMFT 1200 33W 830 U19 PS EM CONVERSION BOX
	Light distribution curve type cone	PL CMFT 1200 33W 830 U19 PS
	Light distribution curve type polar	PL CMFT 1200 24W 830 U19 PS
	Light distribution curve type polar	PL CMFT 1200 28W 830 U19 PS
	Light distribution curve type polar	PL CMFT 1200 33W 830 U19 PS EM CONVERSION BOX
	Light distribution curve type polar	PL CMFT 1200 33W 830 U19 PS
CAD/BIM files		Document name
	BIM Revit 3D	PL_CMFT
	CAD STEP 3D	PL_CMFT_1200
Tender texts		Document name
	Tender documents	PANEL COMFORT 1200 UGR19 PS 33W 830 U19 PS-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854004087	Folding box 1	37 mm x 344 mm x 1,347 mm	3392.00 g	17.14 dm³
4099854004094	Shipping box 4	1,377 mm x 167 mm x 379 mm	15087.00 g	87.15 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.