

PRODUCT DATASHEET LN MAG BATTEN T5 868

LINEAR MAGNETIC BATTEN T5 | Luminaire insert for LED TUBE T5 AC



Areas of application

- Replacement kit for modernizing existing metallic ceiling lights (T8 and T5 Fluorescent) to energy-saving LED technology
- Offices, public buildings
- Supermarkets and department stores
- Industry
- Corridors, foyers, waiting areas



Product benefits

- Retrofitting without completely replacing existing luminaires
- If necessary, the old luminaire may remain installed on the ceiling during the conversion process
- Control gear and wiring may remain in the old luminaire if necessary
- Easy replacement of the LED TUBE T5 AC allows to participate in progress of LED technology over time
- Simple and quick upgrade solution
- Integrated fuse for additional safety
- 5 years guarantee

Product features

- Available in 4 different lengths: 568 mm, 868 mm, 1168 mm and 1468 mm
- Luminaire insert for accommodating one LED TUBE T5 AC 230V
- Suitable for LED TUBE T5 AC, HE or HO, 830/840/865
- Strong neodym magnets



TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	50/60 Hz
Protection class	1
Operating mode	Mains voltage

Dimensions & Weight

Length	868.00 mm
Width	25.00 mm
Height	45.00 mm
Product weight	520.00 g
Cable length	600 mm



LN MAG BATTEN T5 868

Materials & Colors

Product color	White	
Housing color	White	
RAL Color (most similar)	RAL 9016	
Body material	Steel	
Glow Wire Test according to IEC 60695-2-12	850 °C	
Mercury content	0.0 mg	

Application & Mounting

Ambient temperature range	-20+45 °C	
Temperature range at storage	-2080 °C	
Type of connection	Screwless terminal, 3-Pole	
Type of protection	IP20	
Protection class IK (shock resistance)	IK02	
Dimmable	No	

Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	No
Replaceable light source	No
Holder designation	G5

Certificates & Standards

Standards	CE / UKCA / ENEC / CB / DEKRA	
Luminaire with limited surface temperature, "D sign"	No	
Ball shot safe	No	

Additional product data

Number of illuminants	1

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User instruction / safety instructions	LN MAG BATTEN T5	
POF	User instruction / safety instructions	LINEAR MAGNETIC BATTEN T5	
POF	Legal information	Legal Insert LN MAG BATTEN	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF	Legal information	Safety Insert G11205497	
PDF	Declarations of conformity	LN MAG BATTEN T5	
PDF	Declarations of conformity UKCA	LN MAG BATTEN T5	
	Tender texts	Document name	
	render texts	Document name	

LINEAR MAGNETIC BATTEN T5 868-EN

LOGISTICAL DATA


Tender documents


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075821798	Folding box 1	70 mm x 882 mm x 37 mm	605.00 g	2.28 dm ³
4058075821804	Shipping box 10	904 mm x 372 mm x 90 mm	6542.00 g	30.27 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION







References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.