

# PRODUCT DATASHEET LED Star Classic Stick Flame 0.5W 515 Frosted E14

LED STAR STICK | LED lamps, classic stick shape



## Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Attractive lamp appearance

#### **Product features**

- LED alternative to conventional lamps
- Good quality of light; color rendering index  $R_{a:} \ge 80$ ; constant chromaticity



# TECHNICAL DATA

# Electrical data

Nominal wattage	0.5 W
Construction wattage	0.50 W
Nominal voltage	220240 V
Operating mode	AC Mains
Nominal current	12 mA
Type of current	AC
Inrush current	10 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	166
Max. lamp number on MCB B16 A	266
Total harmonic distortion	< 180 %
Power factor $\lambda$	> 0.50


## Photometrical data

Luminous flux	10 lm
Nominal useful luminous flux 90°	10 lm
Luminous efficacy	20 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm Comfort Light
Color temperature	1500 K
Color rendering index Ra	55
Light color	515
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	not applicable
Stroboscope effect metric (SVM)	not applicable

# Light technical data

Beam angle	330 °
Warm-up time (60 %)	< 1.00 s
Starting time	< 0.5 s

# Dimensions & Weight



Overall length	145.00 mm
Diameter	45.00 mm
Maximum diameter	45 mm
Product weight	55.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	50 °C

# Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

# Additional product data

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	No
Certificates & Standards	
Energy consumption	1.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778 RG1	
Country-specific categorizations	
Order reference	LEDSSTICK FLAME
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	LED
Lighting technology used  Non-directional or directional	LED NDLS
Non-directional or directional	NDLS
Non-directional or directional  Mains or non-mains	NDLS MLS
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)	NDLS
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)	NDLS MLS E14
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source	NDLS MLS E14 No
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)	NDLS MLS E14 No No
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope	NDLS MLS E14 No No No
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source	NDLS MLS E14 No No No No No
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield	NDLS MLS E14 No No No No No No
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield  Standby power	NDLS  MLS  E14  No  No  No  No  No  O  NO  NO  NO  NO
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield  Standby power  Networked standby power for CLS	NDLS MLS E14 No No No No No O  NO O  O  O  O  O  O  O  O  O  O  O
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield  Standby power  Networked standby power for CLS  Claim of equivalent power	NDLS  MLS  E14  No  No  No  No  OW  OW  No
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield  Standby power  Networked standby power for CLS  Claim of equivalent power  Length	NDLS  MLS  E14  No  No  No  No  No  No  No  No  No  N
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield  Standby power  Networked standby power for CLS  Claim of equivalent power  Length  Height	NDLS  MLS  E14  No  No  No  No  No  No  No  No  No  N
Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield  Standby power  Networked standby power for CLS  Claim of equivalent power  Length  Height  Width	NDLS  MLS  E14  No  No  No  No  No  No  No  No  No  145.00 mm  45.00 mm

not applicable

Survival factor

Displacement factor	not applicable
LED light source replaces a fluorescent light source	No

## Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

## **DOWNLOAD DATA**

	Documents and certificates	Document name
POF	Declarations of conformity	LED lamp Stick Flame

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075389885	Folding box 1	47 mm x 47 mm x 180 mm	67.00 g	0.40 dm <sup>3</sup>
4058075453135	Shipping box 4	111 mm x 110 mm x 194 mm	317.00 g	2.37 dm <sup>3</sup>
4058075453142	Shipping box 32	240 mm x 238 mm x 417 mm	2987.00 g	23.82 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Frosted E14