

## PRODUCT DATASHEET

# Endura Classic E27 IP65 Orbick Wall Dark Grey

Endura Classic IP65 E27 | Wall luminaires with dark grey aluminum housing, IP65 protection, frosted diffuser and E27 socket



### Areas of application

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

### Product benefits

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

### Product features

- Die-cast aluminum housing
- Frosted diffuser
- Anthracite housing color
- Type of protection: IP65


TECHNICAL DATA

Electrical data

|                  |               |
|------------------|---------------|
| Nominal voltage  | 220...240 V   |
| Mains frequency  | 50...60 Hz    |
| Protection class | I             |
| Operating mode   | Mains voltage |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 200.00 mm |
| Width          | 95.00 mm  |
| Height         | 290.00 mm |
| Product weight | 1000.00 g |



ENDURA CLASSIC ORBICK W E27  
IP65

Materials & Colors

|                                            |                    |
|--------------------------------------------|--------------------|
| Product color                              | Dark gray          |
| Housing color                              | Dark gray          |
| Body material                              | Aluminum           |
| Cover material                             | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |

Application & Mounting

|                                        |                             |
|----------------------------------------|-----------------------------|
| Ambient temperature range              | -20...+40 °C                |
| Type of connection                     | Terminal, 3-Pole (L, N, PE) |
| Type of protection                     | IP65                        |
| Protection class IK (shock resistance) | IK06                        |
| Dimmable                               | No                          |
| Mounting type                          | Surface                     |
| Application environment                | Outdoor                     |
| With light source                      | No                          |
| Replaceable light source               | No                          |
| Holder designation                     | E27                         |

## Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |
| Ball shot safe                                       | No        |

## Additional product data

|                       |                                             |
|-----------------------|---------------------------------------------|
| Product remark        | Maximum bulb wattage: 2 x 18W (2 x 15W LED) |
| Number of illuminants | 2                                           |

## EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

## DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name           |
|------------------------------------------------------------------------------------|----------------------------------------|-------------------------|
|  | User instruction / safety instructions |                         |
|  | Legal information                      | Safety insert G11219578 |
|  | Declarations of conformity             | Endura Classic IP65     |
|  | Declarations of conformity UKCA        | Endura Classic IP65     |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854447525 | Folding box<br>1             | 102 mm x 207 mm x 302 mm             | 1325.00 g    | 6.38 dm <sup>3</sup>  |
| 4099854447532 | Shipping box<br>4            | 440 mm x 230 mm x 335 mm             | 5300.00 g    | 33.90 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.