



PRODUCT DATASHEET

PL FLEX 600 S 30W 840 PS

PANEL FLEX 600 PS | Square recessed panel luminaires with power select feature, for 600 x 600 mm ceiling systems



Areas of application

- Suitable for recessed ceiling systems with grid size of 600 x 600 mm
- Direct replacement for recessed luminaires with fluorescent lamps
- Offices, conference rooms
- Reception areas, foyers, corridors, elevators

Product benefits

- Highly versatile due to selectable power steps (Power Select - PS) on the driver and up to 4860 lm
- Energy savings thanks to high system efficacy: up to 169 lm/W
- High color consistency with SDCM 3
- External driver for extended flexibility and easy installation
- Low flicker light thanks to special electronic control gear
- Tool-free electrical connection due to push button connector
- Through-wiring possible with included connector box
- Decentral emergency lighting possible with separately available LEDVANCE Emergency Conversion Box
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- 7 years guarantee

Product features

- Lifetime (L80/B10): 100,000 h (at 25 °C), (L90/B10): 50,000 h (at 25 °C)
- Suitable for central battery emergency installations acc. to EN 60598-2-22



- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Extruded aluminum frame, metal housing
- Polystyrene diffuser
- Luminaire versions with IoT-ready DALI-2 driver available


TECHNICAL DATA

Electrical data


Nominal wattage	30 W / 25 W / 21 W / 17 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	140.000 mA
Inrush current	11.1 A
Inrush current time T_{h50}	600 μ s
Max. number of luminaires per miniature circuit breaker B16	12
Max. number of luminaires per miniature circuit breaker C10	13
Max. number of luminaires per miniature circuit breaker C16	21
Power factor λ	> 0.90
Total harmonic distortion	< 15 %
Protection class	II
Operating mode	External LED driver

Photometrical data


Luminous flux	4860 lm / 4130 lm / 3510 lm / 2880 lm
Luminous efficacy	162 lm/W / 165 lm/W / 167 lm/W / 169 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	≤ 3 sdc _{cm}
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	110 °




PL FLEX 600 S 17W 4000K 2880lm




PL FLEX 600 S 21W 4000K 3510lm




PL FLEX 600 S 25W 4000K 4130lm




PL FLEX 600 S 30W 4000K 4860lm




PL FLEX 600 S 3W 4000K 400lm
EM BOX




PL FLEX 600 S 17W 4000K 2880lm




PL FLEX 600 S 21W 4000K 3510lm



PL FLEX 600 S 25W 4000K 4130lm



PL FLEX 600 S 30W 4000K 4860lm




PL FLEX 600 S 3W 4000K 400lm
EM BOX

Dimensions & Weight

Length	595.00 mm
--------	-----------

Width	595.00 mm
Height	32.00 mm
Product weight	1500.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polystyrene (PS)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP40/IP20
Protection class IK (shock resistance)	IK02
Dimmable	No
Mounting type	Recessed/Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Mounting length	595.00 mm
Mounting width	595.00 mm

Mounting depth	50 mm
Adjustable	No
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	100000 h ¹⁾
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	50000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	700 mA
ECG - Output ripple current	< 5 %
ECG - Length	125 mm
ECG - Width	60 mm
ECG - Height	30 mm
Recommended control gear	DR DS-P-30/220-240/700 PL FLEX 600

Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EAC / EPD / EL
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	By the end consumer

Additional product data

Added function	MULTI SELECT
----------------	--------------

Accessories Optional

Product image	Product name	EAN
	DR DS-P- 30/220-240/700 PL FLEX 600	4058075843684

Product image	Product name	EAN
	EM CONVERSION BOX	4058075237025
	PANEL Suspension Kit	4058075402928
	PANEL RECESSED MOUNT CLIPS VAL 4x	4058075409859
	PANEL 600 SURFACE MOUNT KIT H75	4058075472914
	PANEL 600 SURFACE MOUNT KIT H70 VAL	4058075402843

EQUIPMENT / ACCESSORIES

- Accessories for several mounting options available
- Connector box with 5-pole terminal included
- Security rope for luminaire included
- Security brackets preinstalled
- External control gear included
- Suitable for use with separate Emergency Conversion Box
- Serviceable luminaire: Upgrades and replacements available

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	PANEL FLEX
 Legal information	LSI PANEL FLEX
 Legal information	Legal Insert PL FLEX

Documents and certificates		Document name
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	EM Insert PL FLEX
	Declarations of conformity	PL FLEX
	Declarations of conformity UKCA	PL FLEX
Photometric and lighting design files		Document name
	IES file (IES)	PL FLEX 600 S 30W 4000K 4860lm
	IES files (IES, additional)	PL FLEX 600 S 17W 4000K 2880lm
	IES files (IES, additional)	PL FLEX 600 S 21W 4000K 3510lm
	IES files (IES, additional)	PL FLEX 600 S 25W 4000K 4130lm
	IES files (IES, additional)	PL FLEX 600 S 3W 4000K 400lm EM BOX
	LDT file (Eulumdat)	PL FLEX 600 S 30W 4000K 4860lm
	LDT files (Eulumdat, additional)	PL FLEX 600 S 17W 4000K 2880lm
	LDT files (Eulumdat, additional)	PL FLEX 600 S 21W 4000K 3510lm
	LDT files (Eulumdat, additional)	PL FLEX 600 S 25W 4000K 4130lm
	LDT files (Eulumdat, additional)	PL FLEX 600 S 3W 4000K 400lm EM BOX
	ULD file (DIALux)	PL FLEX 600 S 30W 840 PS
	ROLF file (RELUX)	PL FLEX 600 S 30W 840 PS
	UGR file (UGR table)	PL FLEX 600 S 17W 4000K 2880lm

Photometric and lighting design files		Document name
	UGR file (UGR table)	PL FLEX 600 S 21W 4000K 3510lm
	UGR file (UGR table)	PL FLEX 600 S 25W 4000K 4130lm
	UGR file (UGR table)	PL FLEX 600 S 30W 4000K 4860lm
	UGR file (UGR table)	PL FLEX 600 S 3W 4000K 400lm EM BOX
	Light distribution curve type cone	PL FLEX 600 S 17W 4000K 2880lm
	Light distribution curve type cone	PL FLEX 600 S 21W 4000K 3510lm
	Light distribution curve type cone	PL FLEX 600 S 25W 4000K 4130lm
	Light distribution curve type cone	PL FLEX 600 S 30W 4000K 4860lm
	Light distribution curve type cone	PL FLEX 600 S 3W 4000K 400lm EM BOX
	Light distribution curve type polar	PL FLEX 600 S 17W 4000K 2880lm
	Light distribution curve type polar	PL FLEX 600 S 21W 4000K 3510lm
	Light distribution curve type polar	PL FLEX 600 S 25W 4000K 4130lm
	Light distribution curve type polar	PL FLEX 600 S 30W 4000K 4860lm
	Light distribution curve type polar	PL FLEX 600 S 3W 4000K 400lm EM BOX

CAD/BIM files		Document name
	BIM Revit 3D	PL FLEX
	CAD STEP 3D	PL FLEX 600

Tender texts		Document name
	Tender documents	PANEL FLEX 600 PS 30W 840 PS-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854276484	Folding box 1	35 mm x 685 mm x 600 mm	1955.00 g	14.39 dm ³
4099854276491	Shipping box 4	705 mm x 160 mm x 625 mm	8901.00 g	70.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

DR 60 SL-30/220-240/70
30W × 20W × 17W × 17W

DR 60 SL-30/220-240/70
30W × 20W × 17W × 17W

PANEL, FLUX 600 × 850¹

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

PL PLEX 600 S 30W 400 PS

DINER

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

DR 60 SL-30/220-240/70

W 60 W 80 W 100 W 120

30 780 400 162

40 800 410 162

50 820 420 167

60 840 430 167

70 860 440 167

80 880 450 167

90 900 460 167

100 920 470 167

110 940 480 167

120 960 490 167

130 980 500 167

140 1000 510 167

150 1020 520 167

160 1040 530 167

170 1060 540 167

180 1080 550 167

190 1100 560 167

200 1120 570 167

210 1140 580 167

220 1160 590 167

230 1180 600 167

240 1200 610 167

250 1220 620 167

260 1240 630 167

270 1260 640 167

280 1280 650 167

290 1300 660 167

300 1320 670 167

310 1340 680 167

320 1360 690 167


CONSIGLIATO DALLO STUDIO DI ARCHITETTURA E INGEGNERIA

PER INFORMAZIONI E PREZZI

PER INFORMAZIONI E PREZZI

PER INFORMAZIONI E PREZZI

PER INFORMAZIONI E PREZZI



– For Guarantee see www.ledvance.com/guarantee

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.