



PRODUCT DATASHEET

PL FLEX 625 DALI S 32W 830 U19

PANEL FLEX 625 UGR<19 DALI | Square recessed panel luminaire with low glare, for 625 x 625 mm ceiling systems and DALI-2 technology



Areas of application

- Suitable for recessed ceiling systems with grid size of 625 x 625 mm
- Direct replacement for recessed luminaires with fluorescent lamps
- Offices, conference rooms
- Reception areas, foyers, corridors, elevators

Product benefits

- Suitable luminaire for VIVARES and other DALI-2 Light Management Systems
- High lumen output with up to 5220 lm
- Energy savings thanks to high system efficacy: up to 160 lm/W
- Good glare reduction ($UGR \leq 19$)
- High color consistency with SDCM 3
- External driver for extended flexibility and easy installation
- Low flicker light thanks to special electronic control gear
- Tool-free electrical connection due to push button connector
- Through-wiring possible with included connector box
- Decentral emergency lighting possible with separately available LEDVANCE Emergency Conversion Box
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- 7 years guarantee

Product features



- IoT-ready luminaire with DALI-2 technology
- Suitable for central battery emergency installations acc. to EN 60598-2-22
- Lifetime (L80/B10): 100,000 h (at 25 °C), (L90/B10): 50,000 h (at 25 °C)
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Extruded aluminum frame, metal housing
- Polystyrene diffuser

TECHNICAL DATA

Electrical data


Nominal wattage	32.00 W ¹⁾
Nominal voltage	220...240 V
Mains frequency	0/50/60 Hz
Nominal current	150.000 mA
Inrush current	4.4 A
Inrush current time T _{h50}	440 µs
Max. number of luminaires per miniature circuit breaker B16	40
Max. number of luminaires per miniature circuit breaker C10	41
Max. number of luminaires per miniature circuit breaker C16	66
Power factor λ	> 0.90
Total harmonic distortion	< 15 %
Protection class	II
Operating mode	External LED driver
Dimming interface	DALI-2 / IoT

¹⁾ The Panel Flex family is fulfilling the technical minimum requirements according to the German BEG subsidy program for energy efficient luminaires


Photometrical data

Luminous flux	5160 lm ¹⁾
Luminous efficacy	155 lm/W ¹⁾
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	≤3 sdcn
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	90 °
UGR	< 19

¹⁾ The Panel Flex family is fulfilling the technical minimum requirements according to the German BEG subsidy program for energy efficient luminaires




PL FLEX DALI 625 S 32W 3000K U19 5160lm



PL FLEX DALI 625 S 32W 3000K U19 5160lm

Dimensions & Weight

Length	620.00 mm
Width	620.00 mm
Height	32.00 mm
Product weight	1700.00 g



Materials & Colors

Product color	White
---------------	-------

Housing color	White
Body material	Aluminum
Cover material	Polystyrene (PS)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP40/IP20
Protection class IK (shock resistance)	IK02
Dimmable	Yes
Type of dimming	DALI2
IoT ready	Support of DALI data type PART 251, 252, 253 ¹⁾
Mounting type	Recessed/Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Mounting length	620 mm
Mounting width	620 mm
Mounting depth	50 mm
Adjustable	No
With light source	Yes
Replaceable light source	No

¹⁾ Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	100000 h ¹⁾
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	50000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	750 mA
ECG - Output ripple current	< 5 %
ECG - Length	110 mm
ECG - Width	75 mm
ECG - Height	25 mm
Recommended control gear	OTi DALI 50/220...240/1A4 NFC

Emergency lighting

Type of Emergency Lighting (EL)	Optional EL unit (battery and controller) for decentral operation available separately / EL certified driver (0Hz / DC operation) for central battery operation included
Wattage in emergency operation mode	6 W
Luminous flux in emergency operation mode	700 lm

Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EAC / EPD / EL
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	By the end consumer

Additional product data

Added function	VIVARES
----------------	---------

Accessories Optional

Product image	Product name	EAN
	DR DS-P- 32/220-240/750 PL FLEX 625	4058075843691
	PANEL 625 RECESSED MOUNT FRAME	4058075402904
	EM CONVERSION BOX	4058075237025

Product image	Product name	EAN
	PANEL Suspension Kit	4058075402928
	PANEL RECESSED MOUNT CLIPS VAL 4x	4058075409859
	OTi DALI 50/220...240/1A4 NFC	4062172061889
	PANEL 625 SURFACE MOUNT KIT H75	4058075472938

EQUIPMENT / ACCESSORIES

- Accessories for several mounting options available
- Connector box with 5-pole terminal included
- Security brackets preinstalled
- External control gear included
- Suitable for use with separate Emergency Conversion Box
- Serviceable luminaire: Upgrades and replacements available

Upgrade and replacement components

Components Light Control		
Product image	Product name	EAN
	MANUAL CONTROL UNIT SELECT DALI-2	4058075837485
	MANUAL CONTROL UNIT SELECT DALI-2 TW	4058075837508

Product image	Product name	EAN
	MANUAL CONTROL UNIT SELECT DALI-2 EXCHANGEABLE COVER TW	4058075837522
	MANUAL CONTROL UNIT TOUCH DALI-2 TW	4058075837560
	MANUAL CONTROL UNIT TOUCH DALI-2	4058075837546
	PUSH CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075837584
	SURFACE MOUNT FRAME	4058075843561
	PUSHBUTTON COUPLER DALI-2	4058075837607
	FLEX CONTROL UNIT IOT DALI-2 HCL TW	4058075841888
	FLEX CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075841901
	FLEX CONTROL UNIT DALI-2 TW	4058075843844
	FLEX CONTROL UNIT REAL-TIME-CLOCK DALI-2 HCL TW	4058075841925
	SENSOR DALI-2 LIGHT/PRESENCE-6 INFRARED CEILING INTEGRATION	4058075837621

Product image	Product name	EAN
	SENSOR DALI-2 LIGHT/PRESENCE-8 INFRARED CEILING INTEGRATION	4058075841949
	SENSOR DALI-2 LIGHT/PRESENCE-40X5 INFRARED CEILING INTEGRATION	4058075843868
	SENSOR DALI-2 LIGHT/PRESENCE-24 INFRARED CEILING MOUNTING	4058075843882
	SENSOR CEILING MOUNTING KIT	4058075843905

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	PANEL FLEX
	Legal information	LSI PANEL FLEX
	Legal information	Legal Insert PL FLEX
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	EM Insert PL FLEX
	Declarations of conformity	PL FLEX
	Declarations of conformity UKCA	PL FLEX
	EU Data Act	DALI LED Driver and Luminaires
	EPD	EPD EN PANEL FLEX DALI


Photometric and lighting design files		Document name
	IES file (IES)	PL FLEX DALI 625 S 32W 3000K U19 5160lm
	IES files (IES, additional)	PL FLEX DALI 625 S 3W 3000K U19 400lm EM BOX
	IES files (IES, additional)	PL FLEX DALI 625 S 6W 3000K U19 750lm EM
	LDT file (Eulumdat)	PL FLEX DALI 625 S 32W 3000K U19 5160lm
	LDT files (Eulumdat, additional)	PL FLEX DALI 625 S 3W 3000K U19 400lm EM BOX
	LDT files (Eulumdat, additional)	PL FLEX DALI 625 S 6W 3000K U19 750lm EM
	ULD file (DIALux)	PL FLEX 625 DALI S 32W 830 U19
	ROLF file (RELUX)	PL FLEX 625 DALI S 32W 830 U19
	UGR file (UGR table)	PL FLEX DALI 625 S 32W 3000K U19 5160lm
	UGR file (UGR table)	PL FLEX DALI 625 S 3W 3000K U19 400lm EM BOX
	UGR file (UGR table)	PL FLEX DALI 625 S 6W 3000K U19 750lm EM
	Light distribution curve type cone	PL FLEX DALI 625 S 32W 3000K U19 5160lm
	Light distribution curve type polar	PL FLEX DALI 625 S 32W 3000K U19 5160lm
CAD/BIM files		Document name
	BIM Revit 3D	PL FLEX
	CAD STEP 3D	PL FLEX 625
Tender texts		Document name
	Tender documents	PANEL FLEX 625 UGR19 DALI 32W 830 U19-EN

LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854276811	Folding box 1	35 mm x 625 mm x 710 mm	2374.00 g	15.53 dm ³
4099854276828	Shipping box 4	737 mm x 179 mm x 657 mm	10818.00 g	86.67 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



DRIVER		W LED W	mA	lm LED W	lm/W
DRIVER DC		30	700	4800	160
PL FLEX 625 S 32W 840 PS		30 <th>600</th> <th>4150</th> <th>138</th>	600	4150	138
PL FLEX 625 S 32W 840 U19 PS		21 <th>600</th> <th>3510</th> <th>167</th>	600	3510	167
PL FLEX 625 S 32W 840 U19 PS		17 <th>415</th> <th>2860</th> <th>166</th>	415	2860	166
PL FLEX 625 S 32W 830 U19 PS		30 <th>700</th> <th>4800</th> <th>160</th>	700	4800	160
PL FLEX 625 S 32W 830 U19 PS		30 <th>600</th> <th>4050</th> <th>135</th>	600	4050	135
PL FLEX 625 S 32W 830 U19 PS		21 <th>600</th> <th>3450</th> <th>164</th>	600	3450	164
PL FLEX 625 S 32W 830 U19 PS		17 <th>415</th> <th>2800</th> <th>166</th>	415	2800	166
PL FLEX 625 S 32W 840 PS		30 <th>700</th> <th>4800</th> <th>160</th>	700	4800	160
PL FLEX 625 S 32W 840 U19 PS		30 <th>600</th> <th>4150</th> <th>138</th>	600	4150	138
PL FLEX 625 S 32W 840 U19 PS		21 <th>600</th> <th>3510</th> <th>167</th>	600	3510	167
PL FLEX 625 S 32W 840 U19 PS		17 <th>415</th> <th>2860</th> <th>166</th>	415	2860	166
PL FLEX 625 S 32W 830 U19 PS		30 <th>700</th> <th>4800</th> <th>160</th>	700	4800	160
PL FLEX 625 S 32W 830 U19 PS		30 <th>600</th> <th>4050</th> <th>135</th>	600	4050	135
PL FLEX 625 S 32W 830 U19 PS		21 <th>600</th> <th>3450</th> <th>164</th>	600	3450	164
PL FLEX 625 S 32W 830 U19 PS		17 <th>415</th> <th>2800</th> <th>166</th>	415	2800	166
PL FLEX 625 S 32W 840 PS		30 <th>700</th> <th>4800</th> <th>160</th>	700	4800	160
PL FLEX 625 S 32W 840 U19 PS		30 <th>600</th> <th>4150</th> <th>138</th>	600	4150	138
PL FLEX 625 S 32W 840 U19 PS		21 <th>600</th> <th>3510</th> <th>167</th>	600	3510	167
PL FLEX 625 S 32W 840 U19 PS		17 <th>415</th> <th>2860</th> <th>166</th>	415	2860	166
PL FLEX 625 S 32W 830 U19 PS		30 <th>700</th> <th>4800</th> <th>160</th>	700	4800	160
PL FLEX 625 S 32W 830 U19 PS		30 <th>600</th> <th>4050</th> <th>135</th>	600	4050	135
PL FLEX 625 S 32W 830 U19 PS		21 <th>600</th> <th>3450</th> <th>164</th>	600	3450	164
PL FLEX 625 S 32W 830 U19 PS		17 <th>415</th> <th>2800</th> <th>166</th>	415	2800	166



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.