

PRODUCT DATASHEET

URB LTRN V 29W ASYM PS 822-827 IP66 BK

URBAN LANTERN ASYMMETRIC | For pathway, bicycle path lighting applications



Areas of application

- Replacement for luminaires with mercury vapor or metal halide lamps
- Streets
- Pedestrian zones
- Parks
- Public areas

Product benefits

- Highly versatile due to selectable CCT and power steps (Power Select - PS)
- Low flicker light thanks to special electronic control gear
- Energy savings thanks to system efficacy of up to 139 lm/W
- Bright, robust and durable

Product features

- Protection class: II
- Lifetime (L80/B10): up to 100,000 h (at 25 °C)
- Type of protection: IP66
- Impact resistance: IK10
- Asymmetric light distribution

TECHNICAL DATA

Electrical data


Nominal wattage	29 W / 25 W / 20.0 W / 15 W ¹⁾
Nominal voltage	220...250 V
Mains frequency	50...60 Hz
Nominal current	70-90-110-130 mA
Inrush current	25.8 A
Inrush current time T _{h50}	300 µs
Max. number of luminaires per miniature circuit breaker B16	8
Max. number of luminaires per miniature circuit breaker C10	8
Max. number of luminaires per miniature circuit breaker C16	13
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	II
Surge capability (L-N)	6 kV
Operating mode	Integrated LED driver

¹⁾ For possible options refer to lumen/power table image

Photometrical data

Luminous flux	3538 lm / 3050 lm / 2440 lm / 1830 lm ¹⁾
Luminous efficacy	122 lm/W ¹⁾
Color temperature	2200 K / 2700 K
Light color (designation)	Warm White
Color rendering index Ra	80
Standard deviation of color matching	5 sdcm
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	165° x 65°


¹⁾ For possible options refer to lumen/power table image



URB LTRN V29/59W ASYMPS

Dimensions & Weight

Diameter	395.00 mm
Height	417.00 mm
Product weight	4200.00 g
Cable length	250 mm



URBAN LANTERN

Materials & Colors

Product color	Black
Housing color	Black
RAL Color (most similar)	RAL 9017
Body material	Aluminum
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	750 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+50 °C
---------------------------	--------------

Temperature range at storage	-35...+80 °C
Type of connection	Cable, 3-pole
Type of protection	IP66
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Post top
Mounting location	Pole
Application environment	Outdoor
Adjustable	No
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	100000 h ¹⁾
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	68000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	765...650...520...390 mA
ECG - Output ripple current	< 20 %

Certificates & Standards

Standards	CE / UKCA / EAC / ENEC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00041-V01.01-EN
Replaceable light source (EPREL)	Not replaceable

Additional product data

Added function	MULTI SELECT
----------------	--------------

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	URBAN LANTERN

Documents and certificates		Document name
	Legal information	Legal Insert URBAN LANTERN
	Legal information	LISO Insert URBAN LANTERN
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	URBAN LANTERN LUM
	Declarations of conformity UKCA	URBAN LANTERN LUM
Photometric and lighting design files		Document name
	IES file (IES)	URBAN LANTERN V 29W ASYM PS 822-827 IP66 BK 2200K
	IES file (IES)	URBAN LANTERN V 29W ASYM PS 822-827 IP66 BK 2700K
	LDT file (Eulumdat)	URBAN LANTERN V 29W ASYM PS 822-827 IP66 BK 2200K
	LDT file (Eulumdat)	URBAN LANTERN V 29W ASYM PS 822-827 IP66 BK 2700K
	ULD file (DIALux)	URB LTRN V 29W ASYMPS822-827 IP66BK
	ROLF file (RELUX)	URB LTRN V 29W ASYMPS822-827 IP66BK
	Light distribution curve type polar	URB LTRN V29/59W ASYMPS
CAD/BIM files		Document name
	BIM Revit 3D	Urban Lantern
	CAD STEP 3D	URBAN LATERN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854287657	Shipping box 1	435 mm x 435 mm x 220 mm	4565.00 g	41.63 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

Part	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Part	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200
Part	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
Part	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.