

## PRODUCT DATASHEET

### Orbis Flame 4X5.5W Click CCT IP44 Chrome

Orbis Flame | Wall/ceiling luminaires with two adjustable color temperatures via wall switch and protection class IP44



#### Areas of application

- Indoor
- Living areas (living rooms, dining rooms, bedrooms etc.)
- Bathrooms (IP44)

#### Product benefits

- Stylish and modern design
- Easy to install and use
- Highly versatile due to selectable CCT
- Long lifetime thanks to LED technology

#### Product features

- Type of protection: IP44
- Lifetime up to 30,000 h
- Color temperature: 3,000 K (Warm White) or 4,000 K (Neutral White)
- Click-CCT version: color temperature adjustable in two steps by repeated switching
- Housing material: aluminum
- Glass diffuser



## TECHNICAL DATA

### Electrical data


|                                                             |                     |
|-------------------------------------------------------------|---------------------|
| Nominal wattage                                             | 22.00 W             |
| Nominal voltage                                             | 220...240 V         |
| Mains frequency                                             | 50...60 Hz          |
| Nominal current                                             | 138.000 mA          |
| Inrush current time $T_{h50}$                               | 192 $\mu$ s         |
| Max. number of luminaires per miniature circuit breaker B16 | 387                 |
| Max. number of luminaires per miniature circuit breaker C10 | 242                 |
| Max. number of luminaires per miniature circuit breaker C16 | 387                 |
| Power factor $\lambda$                                      | > 0.5               |
| Total harmonic distortion                                   | 63 %                |
| Protection class                                            | II                  |
| Operating mode                                              | External LED driver |

### Photometrical data

|                                              |                           |
|----------------------------------------------|---------------------------|
| Luminous flux                                | 1400 lm                   |
| Luminous efficacy                            | 64 lm/W                   |
| Color temperature                            | 3000 ... 4000 K           |
| Light color (designation)                    | Warm White / Cool White   |
| Color rendering index Ra                     | > 80                      |
| Standard deviation of color matching         | $\leq 6$ sdc <sub>m</sub> |
| Photobiological safety group acc. to EN62778 | RG0                       |
| Photobiological safety group acc. to EN62471 | RG0                       |
| Beam angle                                   | 115 °                     |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 350.00 mm |
| Width          | 350.00 mm |
| Height         | 90.00 mm  |
| Product weight | 1900.00 g |



ORBIS FLAME 4X5.5W CLICKCCT  
IP44

Materials & Colors

|                                            |                    |
|--------------------------------------------|--------------------|
| Product color                              | Chrome             |
| Housing color                              | Chrome             |
| Body material                              | Metal Glass        |
| Cover material                             | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |
| Mercury content                            | 0.0 mg             |

Application & Mounting

|                                        |                         |
|----------------------------------------|-------------------------|
| Ambient temperature range              | -20...+40 °C            |
| Temperature range at storage           | -20...+80 °C            |
| Type of connection                     | Terminal, 2-Pole (L, N) |
| Type of protection                     | IP44                    |
| Protection class IK (shock resistance) | IK03                    |
| Dimmable                               | No                      |
| Mounting type                          | Surface                 |
| Application environment                | Indoor                  |
| With light source                      | Yes                     |
| Replaceable light source               | No                      |

Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 30000 h <sup>1)</sup> |
| Number of switching cycles | 15000                 |

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / UKCA       |
| Luminaire with limited surface temperature, "D sign" | No              |
| Ball shot safe                                       | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

## EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

## Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

## DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name           |
|------------------------------------------------------------------------------------|----------------------------------------|-------------------------|
|  | User instruction / safety instructions | ORBIS FLAME CLICK-CCT   |
|  | Legal information                      | Safety insert G11219301 |
|  | Declarations of conformity             | ORBIS FLAME             |
|  | Declarations of conformity UKCA        | ORBIS FLAME             |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854447969 | Folding box<br>1             | 112 mm x 402 mm x 403 mm             | 2867.00 g    | 18.14 dm <sup>3</sup> |
| 4099854447976 | Shipping box<br>3            | 418 mm x 350 mm x 430 mm             | 8600.00 g    | 62.91 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.