

PRODUCT DATASHEET

Orbis Woodburry 300MM 16W 830 Click DIM Wood Decor

Orbis Woodburry | LED ceiling luminaire with wood ring



Areas of application

- Indoor
- Living areas (living rooms, dining rooms, bedrooms etc.)

Product benefits

- Stylish and modern design
- Easy to install and use
- Long lifetime thanks to LED technology

Product features

- Type of protection: IP20
- Lifetime up to 30,000 h
- Click-DIM version: dimmable in three steps by repeated switching
- Color temperature: 3,000 K (Warm White)
- Housing material: plastic and wood



TECHNICAL DATA**Electrical data**


Nominal wattage	16.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	125.000 mA
Inrush current time T_{h50}	3.19 μ s
Max. number of luminaires per miniature circuit breaker B16	102
Max. number of luminaires per miniature circuit breaker C10	64
Max. number of luminaires per miniature circuit breaker C16	102
Power factor λ	> 0.5
Total harmonic distortion	< 150 %
Protection class	I
Operating mode	External LED driver

Photometrical data

Luminous flux	1000 lm
Total luminous flux of contained light sources	2000 lm
Luminous efficacy	62 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥ 80
Standard deviation of color matching	≤ 6 sdcn
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °

Dimensions & Weight

Diameter	300.00 mm
Height	65.00 mm
Product weight	500.00 g



ORBIS WOODBURY 300
16W830CLICKD WD

Materials & Colors

Product color	Wood decor
Housing color	Wood decor
Body material	Metal
Cover material	Plastic
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Mounting type	Surface
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Number of switching cycles	25000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name
	User instruction / safety instructions	ORBIS WOODBURRY
	Legal information	Safety insert G11219601
	Declarations of conformity	ORBIS ALISON ORBIS WOODBURRY ORBIS ALICIA ORBIS YUMMY ORBIS LIVIA ORBIS ALVA
	Declarations of conformity UKCA	ORBIS ALISON ORBIS WOODBURRY ORBIS ALICIA ORBIS YUMMY ORBIS LIVIA ORBIS ALVA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854450846	Folding box 1	77 mm x 322 mm x 323 mm	940.00 g	8.01 dm ³
4099854450853	Shipping box 6	478 mm x 338 mm x 348 mm	5640.00 g	56.22 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.