

PRODUCT DATASHEET EM BULKHEAD E 1.3W 3H EM/AC AT

EMERGENCY BULKHEAD RECTANGULAR | Rectangular EMERGENCY BULKHEAD with IP65 and 3 h standby time



Areas of application

- Antipanic lighting
- Industry
- Corridors, stairways, entrance areas

Product benefits

- Operation of integrated emergency lighting function with long life LiFePO4 battery with 3h battery discharge time
- Easy maintenance with automatic test function or integrated test switch
- Emergency pictograms included in packaging

Product features

- Luminous flux: 200 lm
- Type of protection: IP65
- Battery discharge time: 3 h
- Battery technology: LiFePO4
- Function test: manual (MA) or automatic (AT)
- With integrated test switch for manual testing
- Operation mode: maintained (M) or non-maintained (NM)



TECHNICAL DATA

Electrical data


Nominal wattage	1.30 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz
Nominal current	42.000 mA
Inrush current	6.8 A
Inrush current time T _{h50}	48 μs
Max. number of luminaires per miniature circuit breaker B16	110
Max. number of luminaires per miniature circuit breaker C10	88
Max. number of luminaires per miniature circuit breaker C16	141
Power factor λ	0.3
Protection class	II
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	200 lm	
Luminous efficacy	150 lm/W	
Color temperature	5700 K	
Light color (designation)	Cool Daylight	
Color rendering index Ra	> 80	
Standard deviation of color matching	6 sdcm	
Low flicker	Yes	
Flickering metric (Pst LM)	<1	
Stroboscope effect metric (SVM)	≤ 0,4	
Photobiological safety group acc. to EN62778	RG0	
Beam angle	100 ° x 120 °	

October 29, 2025, 22:45:31 EM BULKHEAD E 1.3W 3H EM/AC AT





EM BULKHEAD E 1,3W 3H EM AC AT

EM BULKHEAD E 1,3W 3H EM AC AT

Dimensions & Weight

Length	355.00 mm
Width	115.00 mm
Height	63.00 mm
Product weight	510.00 g



EM BULKHEAD E 1.3W 3H EM/AC AT

Materials & Colors

Product color	White	
Housing color	White	
Body material	Polycarbonate (PC) Acrylonitrile butadiene styrene (ABS)	
Cover material	Polycarbonate (PC)/ Acrylonitrile Butadiene Styrene (ABS)	

Glow Wire Test according to IEC 60695-2-12	650 °C	
ercury content 0.0 mg		
Application & Mounting		
Ambient temperature range	0+45 °C	
Temperature range at storage	0+35 °C	
Type of connection	Terminal	
Type of protection	IP65	
Protection class IK (shock resistance)	IK06	
Dimmable	No	
Mounting type	Surface	
Mounting location	Ceiling / Wall	
Application environment	Indoor	
Mounting depth	0 mm	
Adjustable	No	
With light source	Yes	
Replaceable light source	No	
ifespan		
Number of switching cycles	50000	
Control gear		
Output current	460 mA	
ECG - Output ripple current	ple current 8 %	
BATTERY		
Type of Battery	LiFePO4	
Battery size [GMS]	Others	
Nominal voltage of battery	3.2 V	
Nominal capacity of battery	1800 mAh	
Battery charging time	24 h	
Emergency lighting		
Type of Emergency Lighting (EL)	EL unit (battery and controller) for decentral operation included	
Facency usuate lighting / Apti magic lighting		

Escape route lighting / Anti-panic lighting

Maintained / Non-maintained

Automatic

October 29, 2025, 22:45:31

EM BULKHEAD E 1.3W 3H EM/AC AT

Area of emergency application

Type of emergency light operation

Type of emergency operation test

Wattage in emergency operation mode	1.3 W
Luminous flux in emergency operation mode	200 lm
Battery life in emergency operation mode	3 h
Integrated test switch	Yes

Certificates & Standards

Standards	CE / CB / EAC / UKCA / ENEC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User instruction / safety instructions	EM BULKHEAD E 1.3W 3H EM/AC AT LEDV	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF	Legal information	EM BULKHEAD E 1.3W 3H EM/AC AT LEDV	
PDF	Legal information	Safety Insert G11218810	
PDF	Legal information	Legal Insert G11231524	
PDF	Declarations of conformity	EM BULKHEAD E 1.3W 3H EM/AC AT	
POF	Declarations of conformity UKCA	EM BULKHEAD E 1.3W 3H EM/AC AT	
	Photometric and lighting design files	Document name	
	Trotomodio and lighting dodign mod	Dodano it Hario	
	IES file (IES)	EM BULKHEAD E 1,3W 3H EM AC AT	
	LDT file (Eulumdat)	EM BULKHEAD E 1,3W 3H EM AC AT	

Photometric and lighting design files	Document name	
UGR file (UGR table)	EM BULKHEAD E 1,3W 3H EM AC AT	
Light distribution curve type cone	EM BULKHEAD E 1,3W 3H EM AC AT	
Light distribution curve type polar	EM BULKHEAD E 1,3W 3H EM AC AT	
CAD/BIM files	Document name	
CAD STEP 3D	EM BLKH E	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854230677	Folding box 1	115 mm x 70 mm x 360 mm	596.00 g	2.90 dm ³
4099854230684	Shipping box 10	605 mm x 375 mm x 174 mm	6920.00 g	39.48 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.