

PRODUCT DATASHEET

Decor Puck Floor 12W 930 Black

Decor Puck | Decorative luminaires made of metal with integrated LED



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms

Product benefits

- Geometric shapes meet even illumination
- Minimalistic style fits to every room
- Different types of luminaires with the same design language maintain a consistent style at home
- Two options for easy wall installation (via EU plug on cable or direct wiring)
- Movable head for directional light
- Easy mounting
- High CRI value of 90 for natural-looking colors

Product features

- Housing material: metal
- High-power LED
- Color temperature: 3,000 K
- Optional 1.5m cable provided with fitted EU plug (only for wall luminaire)



TECHNICAL DATA

Electrical data


Nominal wattage	12.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Inrush current	5.3 A
Inrush current time T _{h50}	46 µs
Max. number of luminaires per miniature circuit breaker C10	22
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	590 lm
Total luminous flux of contained light sources	1050 lm
Luminous efficacy	50 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 90
Beam angle	120 °

Dimensions & Weight

Length	250.00 mm
Width	375.00 mm
Height	1430.00 mm
Product weight	4250.00 g
Cable length	1800 mm



DECOR PUCK FLOOR 12W 930 BK

Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	No
Mounting type	Standing
Mounting location	Floor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
---------------------------	-----------------------

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE
-----------	----



Additional product data

Number of illuminants	1
-----------------------	---

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- The external flexible cable or cord of this luminaire cannot be replaced; if the cord is damaged, the luminaire shall be destroyed.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR PUCK TABLE+FLOOR
	Declarations of conformity	DECOR LUM SERIES 1 PUCK_KYOTO

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075846487	Folding box 1	152 mm x 322 mm x 762 mm	4894.00 g	37.30 dm ³
4058075846494	Shipping box 2	782 mm x 342 mm x 330 mm	10970.00 g	88.26 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.