


## PRODUCT DATASHEET

### Decor Puck 1XPendant 12W 930 Black

Decor Puck | Decorative luminaires made of metal with integrated LED



#### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms

#### Product benefits

- Geometric shapes meet even illumination
- Minimalistic style fits to every room
- Different types of luminaires with the same design language maintain a consistent style at home
- Two options for easy wall installation (via EU plug on cable or direct wiring)
- Movable head for directional light
- Easy mounting
- High CRI value of 90 for natural-looking colors

#### Product features

- Housing material: metal
- High-power LED
- Color temperature: 3,000 K
- Optional 1.5m cable provided with fitted EU plug (only for wall luminaire)



TECHNICAL DATA

Electrical data


Nominal wattage	12.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	120.000 mA
Inrush current	0.35 A
Inrush current time T <sub>h50</sub>	46 µs
Max. number of luminaires per miniature circuit breaker B16	36
Max. number of luminaires per miniature circuit breaker C10	22
Max. number of luminaires per miniature circuit breaker C16	36
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	590 lm
Luminous efficacy	50 lm/W
Color temperature	3000 K
Color rendering index Ra	> 90
Beam angle	120 °

Dimensions & Weight

Diameter	230.00 mm
Height	1500.00 mm
Product weight	1300.00 g



DECOR PUCK 1XPENDANT 12W  
930 BK

## Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

## Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Suspended
Mounting location	Ceiling
Application environment	Indoor
With light source	Yes
Replaceable light source	No

## Certificates & Standards

Standards	CE / UKCA
-----------	-----------


## Additional product data



Number of illuminants	1
-----------------------	---

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- The external flexible cable or cord of this luminaire cannot be replaced; if the cord is damaged, the luminaire shall be destroyed.

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR PUCK PENDANT

Documents and certificates		Document name
	Declarations of conformity	DECOR PUCK_KYOTO_930
	Declarations of conformity UKCA	DECOR LUM PUCK_KYOTO PENDAT 930

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075846524	Folding box 1	152 mm x 282 mm x 302 mm	1589.00 g	12.94 dm³
4058075846531	Shipping box 4	587 mm x 327 mm x 330 mm	7294.00 g	63.34 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.