

PRODUCT DATASHEET

TR SP XR DA V 30W 930 24DEG BK

TRACKLIGHT SPOT XR DALI | 3-phase tracklight spot with exchangeable reflector and DALI-2 technology



Areas of application

- Direct replacement for luminaires using HID lamps
- Accent lighting
- Galleries, museums
- Shops, changing rooms, shop windows
- Hotels, restaurants

Product benefits

- Reflector easily replaceable thanks to bayonet catch and rubber suction pad
- No distraction from the illuminated objects thanks to the reduced design
- Low flicker light thanks to special electronic control gear
- Good glare reduction ($UGR \leq 19$)

Product features

- Compact tracklight spot with in-track DALI-2 driver
- Rotation angle: 350°, tilt angle: 90°
- Available with color temperature 3000 K or 4000 K
- Color rendering index CRI 90
- Initial color consistency: ≤ 3 SDCM
- Equipped with reflectors with 24° beam angle
- Durable die-cast aluminum housing
- Available in matt white (like RAL9003), matt black (like RAL9005)
- Luminaire efficacy: up to 120 lm/W




TECHNICAL DATA**Electrical data**


Nominal wattage	30.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	750.000 mA
Inrush current	0.86 A
Inrush current time T_{h50}	62 μ s
Max. number of luminaires per miniature circuit breaker B16	94
Max. number of luminaires per miniature circuit breaker C10	58
Max. number of luminaires per miniature circuit breaker C16	94
Power factor λ	> 0.90
Total harmonic distortion	< 15 %
Protection class	I
Surge capability (L-N)	1000 V
Operating mode	Integrated LED driver

Photometrical data


Luminous flux	3600 lm
Luminous efficacy	120 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 90
Standard deviation of color matching	≤ 3 sdc _m
Luminous intensity	4100 cd
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	15° / 24° / 36° / 50 °
UGR	< 20




TR SP XR DA V 30W 930 BK 15D




TR SP XR DA V 30W 930 BK 24D




TR SP XR DA V 30W 930 BK 36D




TR SP XR DA V 30W 930 BK 50D




TR SP XR DA V 30W 930 BK 15D



TR SP XR DA V 30W 930 BK 24D




TR SP XR DA V 30W 930 BK 36D



TR SP XR DA V 30W 930 BK 50D

Dimensions & Weight

Diameter	80.00 mm
Length	189.00 mm
Height	240.00 mm
Product weight	660.00 g



TR SP XR DA V 30W 24DEG

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Adapter, 3-phase
Type of protection	IP20/IP20
Protection class IK (shock resistance)	IK02
Dimmable	Yes
Type of dimming	DALI
Mounting type	Surface
Mounting location	Mounting track
Application environment	Indoor
Adjustable	Yes
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	750 mA
ECG - Output ripple current	< 3 %

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

Certificates & Standards

Standards	CE / ENEC / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Available from September 2025
Added function	VIVARES

Accessories Optional

Product image	Product name	EAN
	TR SP REFLECTOR V 30W 15DEG	4099854616846
	TR SP REFLECTOR V 30W 36DEG	4099854616860
	TR SP REFLECTOR V 30W 50DEG	4099854616884

EQUIPMENT / ACCESSORIES

- Accessory reflectors with 15°, 36° or 50° beam angle available

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	G11247137 TRACKLIGHT SPOT XR DALI

Documents and certificates		Document name
	Legal information	Safety Insert G11218810
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	TRACKLIGHT SPOT
	Declarations of conformity UKCA	TRACKLIGHT SPOT
	Certificates	ENEC TR SP ZOOM
Photometric and lighting design files		Document name
	IES file (IES)	TR SP XR DA V 30W 930 BK 15D
	IES file (IES)	TR SP XR DA V 30W 930 BK 24D
	IES file (IES)	TR SP XR DA V 30W 930 BK 36D
	IES file (IES)	TR SP XR DA V 30W 930 BK 50D
	LDT file (Eulumdat)	TR SP XR DA V 30W 930 BK 15D
	LDT file (Eulumdat)	TR SP XR DA V 30W 930 BK 24D
	LDT file (Eulumdat)	TR SP XR DA V 30W 930 BK 36D
	LDT file (Eulumdat)	TR SP XR DA V 30W 930 BK 50D
	UGR file (UGR table)	TR SP XR DA V 30W 930 BK 15D
	UGR file (UGR table)	TR SP XR DA V 30W 930 BK 24D
	UGR file (UGR table)	TR SP XR DA V 30W 930 BK 36D
	UGR file (UGR table)	TR SP XR DA V 30W 930 BK 50D
	Light distribution curve type cone	TR SP XR DA V 30W 930 BK 15D




Photometric and lighting design files		Document name
	Light distribution curve type cone	TR SP XR DA V 30W 930 BK 24D
	Light distribution curve type cone	TR SP XR DA V 30W 930 BK 36D
	Light distribution curve type cone	TR SP XR DA V 30W 930 BK 50D
	Light distribution curve type polar	TR SP XR DA V 30W 930 BK 15D
	Light distribution curve type polar	TR SP XR DA V 30W 930 BK 24D
	Light distribution curve type polar	TR SP XR DA V 30W 930 BK 36D
	Light distribution curve type polar	TR SP XR DA V 30W 930 BK 50D
CAD/BIM files		Document name
	CAD STEP 3D	TL XR DA V 30W

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854616693	Folding box 1	191 mm x 242 mm x 100 mm	806.00 g	4.62 dm ³
4099854616709	Shipping box 4	400 mm x 262 mm x 230 mm	3720.00 g	24.10 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION





References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.