

PRODUCT DATASHEET

TR SP HOUSING E GU10 WT

TRACKLIGHT SPOT GU10 | 3-phase tracklight spot with GU10 socket base



Areas of application

- Shops, changing rooms, shop windows
- Hotels, restaurants

Product benefits

- Socket compatible for lamp power up to 10W

Product features

- Base: GU10
- Rotation angle: 350°, tilt angle: 90°
- Durable die-cast aluminum housing
- Available in matt white (like RAL9003), matt black (like RAL9005)



TECHNICAL DATA

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	II

Dimensions & Weight

Diameter	58.00 mm
Length	58.00 mm
Width	58.00 mm
Height	145.00 mm
Product weight	151.00 g



TR SP HOUSING E GU10 WT

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9003
Body material	Aluminum
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Adapter, 3-phase
Protection class IK (shock resistance)	IK02
Dimmable	No
Mounting type	Surface
Mounting location	Mounting track

Application environment	Indoor
Adjustable	Yes
With light source	No
Replaceable light source	No
Holder designation	GU10

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	G11248823 TRACKLIGHT SPOT HOUSING E GU10
 Legal information	Informationstext 18 Abs 4 ElektroG
 Declarations of conformity	TRACKLIGHT SPOT HOUSING E GU10
 Declarations of conformity UKCA	TRACKLIGHT SPOT HOUSING E GU10

Tender texts	Document name
 Tender documents	TRACKLIGHT SPOT GU10 GU10 WT-en

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854590023	Folding box 1	67 mm x 92 mm x 163 mm	185.00 g	1.00 dm ³
4099854590030	Shipping box 20	385 mm x 350 mm x 190 mm	4347.00 g	25.60 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.