

PRODUCT DATASHEET

LISOEV 1074x29 39 40W 930 A55x55 BK

LINEAR INDIVILED LIGHT SOURCES ASYMMETRIC | Upgrade or replacement light source unit for asymmetric light distribution



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- Easy installation, no tools required for connection
- Homogenous light distribution and reduced glare ($UGR \leq 19$) thanks to IndiviLED® optics
- High performance with CRI90

Product features

- Asymmetric light distribution
- Lifetime (L80/B10): 70,000 h (at 25 °C)
- Beam angle: 90°


TECHNICAL DATA

Electrical data

Nominal wattage	40.00 W
Nominal voltage	45 V
Nominal current	800.000 mA

Photometrical data

Luminous flux	3950 lm
Luminous efficacy	99 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥90
Standard deviation of color matching	3 sdcm
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	55 ° x 55 °
UGR	19



LISOEV 1074X29 39 40W 930
A55x55 BK LEDV 800mA

Dimensions & Weight

Length	1074.00 mm
Width	29.00 mm
Height	19.00 mm
Product weight	369.00 g



1 2m DIRECT LED MODULE

Materials & Colors

Product color	Black
Housing color	Black

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Push-in clamp
Type of protection	IP20
Dimmable	No

Lifespan

Lifespan L70/B50 at 25 °C	100000 h
Lifespan L80/B10 at 25 °C	70000 h
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	25000

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC
-----------	---------------------------------------

Additional product data

Product remark	Available from September 2025
----------------	-------------------------------

Safety advice

- All electrical connections must be made by a qualified person.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	User instruction G11244437
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Safety Insert G11218810
	Legal information	Legal Insert G11244392
	Legal information	LSI insert G11244301
Photometric and lighting design files		Document name
	IES file (IES)	LISOEV 1074X29 39 40W 930 A55x55 BK LEDV 800mA
	LDT file (Eulumdat)	LISOEV 1074X29 39 40W 930 A55x55 BK LEDV 800mA
	Light distribution curve type polar	LISOEV 1074X29 39 40W 930 A55x55 BK LEDV 800mA
CAD/BIM files		Document name
	CAD STEP 3D	LN INDV DIRECT G2 LISOEV 1200 ASYM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854652233	Folding box 1	36 mm x 1,082 mm x 26 mm	455.00 g	1.01 dm ³
4099854652240	Shipping box 10	1,094 mm x 184 mm x 67 mm	5104.00 g	13.49 dm ³
4099854652257	Shipping box 20	1,114 mm x 204 mm x 158 mm	11316.00 g	35.91 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

DIRECT		INDIRECT		
EAN	LOREV	EAN	LOREV	EA1 LINEAR INdEXED EAN
430905405009	10747 94 500 000 000 000	43090540501676	100001 1 100 000 000 000 000	43090540500903
				4309054050167603
				43090540500904
				4309054050167604
				43090540500905
430905405080	10747 94 500 000 000 000	43090540508000	100001 1 100 000 000 000 000	43090540508003
				43090540508004
				43090540508005
				43090540508006
				43090540508007
4309054050110	100001 1 100 000 000 000 000	43090540501100	100001 1 100 000 000 000 000	43090540501103
				43090540501104
				43090540501105
				43090540501106
				43090540501107
4309054050118	100001 1 100 000 000 000 000	43090540501180	100001 1 100 000 000 000 000	43090540501183
				43090540501184
				43090540501185
				43090540501186
				43090540501187
4309054050230	10747 94 500 000 000 000	43090540502300	100001 1 100 000 000 000 000	43090540502303
				43090540502304
				43090540502305
				43090540502306
				43090540502307
4309054050084	10747 94 500 000 000 000	43090540500840	100001 1 100 000 000 000 000	43090540500843
				43090540500844
				43090540500845
				43090540500846
				43090540500847

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.