


## PRODUCT DATASHEET

### Endura Style IP65 Wall Idar Dark Grey

ENDURA® Style IP65 Wall | Wall luminaires with dark grey housing and IP65 protection



---

#### Areas of application

- Decorative outdoor lighting
- Building facades
- Entrance lighting
- Patios, balconies

---

#### Product benefits

- Easy and quick installation

---

#### Product features

- Durable housing material
- Type of protection: IP65

TECHNICAL DATA

Electrical data

|                                                             |               |
|-------------------------------------------------------------|---------------|
| Nominal wattage                                             | 7.50 W        |
| Nominal voltage                                             | 220...240 V   |
| Mains frequency                                             | 50...60 Hz    |
| Nominal current                                             | 37.000 mA     |
| Max. number of luminaires per miniature circuit breaker B16 | 63            |
| Max. number of luminaires per miniature circuit breaker C10 | 53            |
| Max. number of luminaires per miniature circuit breaker C16 | 86            |
| Power factor $\lambda$                                      | > 0.5         |
| Total harmonic distortion                                   | < 70 %        |
| Protection class                                            | II            |
| Operating mode                                              | Mains voltage |

Photometrical data

|                                                |            |
|------------------------------------------------|------------|
| Luminous flux                                  | 340 lm     |
| Total luminous flux of contained light sources | 900 lm     |
| Luminous efficacy                              | 45 lm/W    |
| Color temperature                              | 3000 K     |
| Light color (designation)                      | Warm White |
| Color rendering index Ra                       | 80         |
| Standard deviation of color matching           | 6 sdcn     |
| Photobiological safety group acc. to EN62778   | RG1        |
| Beam angle                                     | 103 °      |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 113.00 mm |
| Width          | 51.00 mm  |
| Height         | 220.00 mm |
| Product weight | 385.00 g  |



ENDURA STYLE IDAR WALL IP65  
DG

Materials & Colors

|                                            |                    |
|--------------------------------------------|--------------------|
| Product color                              | Dark gray          |
| Housing color                              | Dark gray          |
| Body material                              | Polycarbonate (PC) |
| Cover material                             | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |
| Mercury content                            | 0.0 mg             |

### Application & Mounting

|                                        |                         |
|----------------------------------------|-------------------------|
| Ambient temperature range              | -20...+45 °C            |
| Type of connection                     | Terminal, 2-Pole (L, N) |
| Type of protection                     | IP65                    |
| Protection class IK (shock resistance) | IK06                    |
| Dimmable                               | No                      |
| Mounting type                          | Surface                 |
| Application environment                | Outdoor                 |
| With light source                      | Yes                     |
| Replaceable light source               | No                      |

### Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 30000 h <sup>1)</sup> |
| Number of switching cycles | 15000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / UKCA       |
| Luminaire with limited surface temperature, "D sign" | No              |
| Ball shot safe                                       | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

### DOWNLOAD DATA

| Documents and certificates                                                       |                                        | Document name                 |
|----------------------------------------------------------------------------------|----------------------------------------|-------------------------------|
|  | User instruction / safety instructions | ENDURA STYLE IDAR             |
|  | Legal information                      | Safety insert G11219279       |
|  | Declarations of conformity             | CE Declaration Endura Style   |
|  | Declarations of conformity UKCA        | UKCA Declaration Endura Style |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854444470 | Folding box<br>1             | 62 mm x 127 mm x 234 mm              | 495.00 g     | 1.84 dm <sup>3</sup>  |
| 4099854444487 | Shipping box<br>4            | 272 mm x 142 mm x 264 mm             | 1980.00 g    | 10.20 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.