

# PRODUCT DATASHEET SMART+ ZB PLUG EU

SMART+ plugs with Zigbee technology | Plug with smart socket to control non smart devices with ZigBee technology



#### Areas of application

 Wherever non-smart devices need to be integrated into compatible smart home systems

## Product benefits

- Small design, compatible with all types of sockets and does not interfere with neighboring sockets
- Integrates conventional electric equipment into compatible smart home systems
- Enables switching of conventional light sources and other electric devices
- Monitors energy usage of connected devices and tracks the energy consumption

## **Product features**

- Control via compatible smart home system, or on/off button on the device
- Control via voice control available: Google Assistant or Amazon Alexa, depending on the smart home system in use
- Network protocol: ZigBee 3.0
- Scheduling
- $-\,$  High switching power: up to 2,300 W / 10 A
- Energy meter
- For full functionality, connection to a compatible smart home System (gateway and app) required



### **TECHNICAL DATA**

### Electrical data

Nominal voltage	230 V
Mains frequency	50 Hz

# Dimensions & Weight



Product weight	82.00 g
Length	82 mm
Width	55 mm
Height	55 mm

# Lifespan

Number of switching cycles 100000
-----------------------------------

## Colors & materials

Product color	White
Body material	Plastic

## Temperatures & operating conditions

Ambient temperature range -2040 °C
------------------------------------

## Capabilities

Compatible smart home technology	Amazon Alexa / Google Assistant / Philips Hue
Certificates & Standards	

Protection class	T. Control of the con
Type of protection	IP20

### **EQUIPMENT / ACCESSORIES**

- Control via app requires a compatible Smart home system

### Safety advice

- Disconnect devices which generate heat from the mains, i.e. from the SMART+ Plug, after use in order to avoid them being accidentally switched on.
- Very high capacitive and inductive loads may in some cases lead to destruction of the device or reduction in the number of switching cycles.
- Do not use the SMART+ Plug in conjunction with medical equipment.
- To be connected to an automatic circuit breaker (for max. 10 A)
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### **DOWNLOAD DATA**

	Documents and certificates	Document name
PDF	Extended installation guide	SMART+ PLUG EU
PDF	Declarations of conformity	SMART ZB PLUG
PDF	EU Data Act	SMART ZigBee Plugs

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075729261	Folding box	61 mm x 96 mm x 154 mm	199.00 g	0.90 dm <sup>3</sup>
4058075729278	Shipping box 4	211 mm x 167 mm x 141 mm	917.00 g	4.97 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.