

PRODUCT DATASHEET P STICK 60 FR 8 W/2700 K E27

PARATHOM® STICK | LED lamps, classic stick shape



Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Low energy consumption
- Attractive lamp appearance
- Instant 100 % light, no warm-up time

Product features

- LED alternative to conventional lamps
- Lifetime up to 15,000 h
- Not dimmable
- Good quality of light; color rendering index $R_{a}\!\!:$ \geq 80; constant chromaticity






TECHNICAL DATA

Electrical data

Nominal wattage	8 W
Construction wattage	8.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	58 mA
Type of current	AC
Inrush current	10.2 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	172
Max. lamp number on MCB B16 A	310
Total harmonic distortion	105 %
Power factor λ	> 0.50

Photometrical data

Luminous flux	806 lm
Nominal useful luminous flux 90°	806 lm
Luminous efficacy	100 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.9



349927_2700K_Evl_5630.eps

Light technical data

Beam angle	200°
Warm-up time (60 %)	0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	116.00 mm
Diameter	36.00 mm
Maximum diameter	38 mm
Product weight	29.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	82 °C

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	F 1)
Energy consumption	8.00 kWh/1000h
Type of protection	IP20
Standards	ROHS 2.0 / REACH / CE
Photobiological safety group acc. to EN62778	RG0
Order reference	LEDPSTICK60 8W/
	LEDF3TICK00 6W/
	-40+80 °C
OGISTICAL DATA Temperature range at storage	
OGISTICAL DATA Temperature range at storage	
COGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015	-40+80 °C
OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used	-40+80 °C
COGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional	-40+80 °C LED NDLS
Concentration of the control of the	-40+80 °C LED NDLS MLS
COGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface)	-40+80 °C LED NDLS MLS E27
OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	-40+80 °C LED NDLS MLS E27 No
Color-tuneable light source	-40+80 °C LED NDLS MLS E27 No No
Color-tuneable light source Envelope Conglistical Data Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope	-40+80 °C LED NDLS MLS E27 No No
Colstical Data Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source	-40+80 °C LED NDLS MLS E27 No No No
Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source Anti-glare shield	-40+80 °C LED NDLS MLS E27 No No No No No No
Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source Anti-glare shield Correlated colour temperature type	-40+80 °C LED NDLS MLS E27 No No No No SINGLE_VALUE

116.00 mm

36.00 mm

Length

Height

Width	36.00 mm
Chromaticity coordinate x	0.458
Chromaticity coordinate y	0.410
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.50
LED light source replaces a fluorescent light source	No
EPREL ID	523290
Model number	AC31132

DOWNLOAD DATA

	Documents and certificates	Document name
POF	Declarations of conformity	LED Stick lamp

Photometric and lighting design files	Document name
Spectral power distribution	349927_2700K_EvI_5630.eps

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075593374	Folding box	36 mm x 36 mm x 120 mm	37.00 g	0.16 dm ³
4058075593381	Shipping box 10	197 mm x 83 mm x 135 mm	467.00 g	2.21 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.