

## PRODUCT DATASHEET

### P GLOBE 75 9 W/2700 K E27

PARATHOM® CLASSIC GLOBE DIM | LED lamps, classic ball shape



#### Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lamps with innovative LED "filament" technology
- Lower energy consumption than incandescent or halogen lamps
- Can be easily fitted instead of ordinary light bulbs
- Instant 100 % light, no warm-up time

#### Product features

- Dimmable (with many common dimmers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim))
- Lifetime up to 15,000 h
- Beam angle: up to 360°
- Professional LED lamps for line voltage
- Lamp made of glass
- Good quality of light; color rendering index  $R_a \geq 80$ ; constant chromaticity



---

**TECHNICAL DATA****Electrical data**

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	75 W
Nominal current	52 mA
Type of current	AC
Inrush current	0.12 A
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Max. lamp number on MCB B10 A	65
Max. lamp number on MCB B16 A	105
Power factor $\lambda$	> 0.50


**Photometrical data**

Luminous flux	1055 lm
Nominal useful luminous flux 90°	1055 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcn
Rated LLMF at 6,000 h	0.80

**Light technical data**

Beam angle	320 °
Warm-up time (60 %)	· 0.50 s
Starting time	< 0.5 s

**Dimensions & Weight**



Overall length	138.00 mm
Diameter	95.00 mm
Maximum diameter	95 mm
Product weight	62.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	65 °C

Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Dimmable (with many common dimmers, see also <a href="http://www.ledvance.com/dim">www.ledvance.com/dim</a> ) / All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes
----------	-----

## Certificates &amp; Standards

Energy efficiency class	A++ <sup>1)</sup>
Energy consumption	9.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778	RG0

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

## Country-specific categorizations

Order reference	LEDPG9575D 9W/8
-----------------	-----------------

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	138.00 mm
Height	95.00 mm
Width	95.00 mm

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075439030	Folding box 1	110 mm x 110 mm x 158 mm	118.00 g	1.91 dm <sup>3</sup>
4058075439047	Shipping box 6	342 mm x 231 mm x 175 mm	938.00 g	13.83 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.