

# PRODUCT DATASHEET P CLAS A 40 4 W/4000 K E27

PARATHOM® DAYLIGHT SENSOR CLASSIC A | Special LED lamps with daylight sensor, classic bulb shape



#### Areas of application

- Wherever constant lighting is necessary at night
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Short payback period thanks to low energy consumption and maintenance costs
- Energy-saving lighting solution thanks to automatic switch off at daylight
- Safety through automatic switch-on at darkness
- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time
- Light sensors detect daylight on the basis of the spectral distribution

#### **Product features**

- LED alternative to conventional lamps
- Not dimmable
- Good quality of light; color rendering index  $R_{a:} \ge 80$ ; constant chromaticity





# TECHNICAL DATA

# Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	34 mA
Type of current	AC
Inrush current	2 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	110
Max. lamp number on MCB B16 A	160
Power factor λ	> 0.50

## Photometrical data

Luminous flux	470 lm
Nominal useful luminous flux 90°	470 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

# Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	105.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm

Product weight	30.00 g
Temperatures & operating conditions	
Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	60 °C
Lifespan	
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	A++ 1)
Energy consumption	4.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778	RG0
Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E     Country-specific categorizations	(lowest efficiency)
Order reference	LEDPCLA40DS 4W/
Energy labelling regulation data acc EU 2019/2015	
Light source cap-type (or other electric interface)	E27
1	405.00

105.00 mm

Length

Height	60.00 mm
Width	60.00 mm

# Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075162266	Folding box 1	60 mm x 60 mm x 111 mm	44.00 g	0.40 dm <sup>3</sup>
4058075162273	Shipping box 10	315 mm x 131 mm x 126 mm	510.00 g	5.20 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.