

# PRODUCT DATASHEET HALOLINE SST 120 W 240 V R7S

HALOLINE® SUPERSTAR | Double ended halogen lamps with tube base



#### Areas of application

- Entrance lighting
- Pathway lighting
- Garden lighting
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Ideal for emphasizing and accentuating the structure of a room

## **Product benefits**

- Brilliant accent lighting
- Direct replacement for standard tubular halogen lamps
- $\,$  Significantly lower  $\mbox{CO}_2$  emissions compared to standard version
- Lower thermal output (compared with the standard reference product)
- No transformer required

## Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index Ra: 100
- Base: R7s




# TECHNICAL DATA

# Electrical data

Nominal wattage	120 W
Construction wattage	120.00 W
Nominal voltage	240 V
Nominal current	500 mA

# Photometrical data

Luminous flux	2245 lm
Luminous efficacy	18 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	100
Light color	1030
UV protection	No



349635\_HAL\_ohne\_UVS

## Light technical data

Starting time	0 s

# Dimensions & Weight

Overall length	118.00 mm
Diameter	12.00 mm
Product weight	7.2 g

# Lifespan

Lifespan L70/B50 at 25 °C	2000 h

# Additional product data

	FRODUCT DATASTILL
Base (standard designation)	R7s
Mercury-free	Yes
Design / version	Tube
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / For outdoor applications and operation in damp locations special approved fixtures are required / Technical and light values are subject to be changed
Capabilities	
Dimmable	Yes
Burning position	Any
Certificates & Standards	
Energy efficiency class	G
Energy consumption	120.00 kWh/1000h
Country-specific categorizations	
ILCOS	HDG-120-240-R7s-114,2
Order reference	64696 ECO SST
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	R7s
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No

0 W

No

not applicable

118.00 mm

12.00 mm

12.00 mm

0,437

0,404

Standby power

Length

Height

Width

Networked standby power for CLS

Claim of equivalent power

Chromaticity coordinate x

Chromaticity coordinate y

Beam angle correspondence	SPHERE_360
Displacement factor	1
EPREL ID	714435,1554001
Model number	AC35332,AC51811

# Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

### **DOWNLOAD DATA**

Photometric and lighting design files	Document name	
Spectral power distribution	349635_HAL_ohne_UVS	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321977694	Blister 1	14 mm x 140 mm x 120 mm	18.20 g	0.24 dm <sup>3</sup>
4058075666993	Bundle 2	28 mm x 140 mm x 120 mm	33.00 g	0.47 dm <sup>3</sup>
4008321977700	Shipping box 10	147 mm x 146 mm x 130 mm	240.00 g	2.79 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.