

PRODUCT DATASHEET NAV-T 70 W SUPER 4Y

VIALOX® NAV®-T SUPER 4Y® 50...400 W | High-pressure sodium vapor lamps for open and enclosed luminaires



Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- Very high luminous efficacy
- Very good luminous flux maintenance throughout the life of the lamp
- $-\,$ Energy savings of up to 50 % when replacing mercury vapor lamps (HQL)
- Optimum energy efficiency on POWERTRONIC® PTo 3DIM ECGs

Product features

- Lamp survival factor: 95 % after 16,000 h burning time
- Lamp maintenance factor: ≥ 80 % after 16,000 h burning time (according to DIN 13201)
- Service lifetime: 4 years (at approx. 11 h/day)
- Dimmable on conventional control gears and electronic control gears





TECHNICAL DATA


Electrical data

Nominal wattage	70 W	
onstruction wattage 76.90 W		
Nominal voltage	90 V	
Ignition voltage	1.8/5.0 kVp ¹⁾	
Operating mode	Conventional control gear (CCG) and ignitor, Electronic control gear (ECG)	
Nominal current	980 mA	
PFC capacitor at 50 Hz	12 µF	

¹⁾ Minimum / Maximum

Photometrical data

Luminous flux	6400 lm
Luminous efficacy	83 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.92
Rated LLMF at 4,000 h	0.91
Rated LLMF at 6,000 h	0.90
Rated LLMF at 8,000 h	0.89
Rated LLMF at 12,000 h	0.88
Rated LLMF at 16,000 h	0.86
Rated LLMF at 20,000 h	0.85
UV protection	No



384084_NAV_SUPER_4Y

Dimensions & Weight

Overall length	155.00 mm
Light center length (LCL)	104,0 mm
Diameter	36,0 mm
Product weight	60.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	310 °C
Maximum permitted base edge temperature	210 °C

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.98
Rated lamp survival factor at 6,000 h	0.98
Rated lamp survival factor at 8,000 h	0.97
Rated lamp survival factor at 12,000 h	0.96
Rated lamp survival factor at 16,000	0.95
Rated lamp survival factor at 20,000 h	0.90
Lifespan B10	20000 h
Lifespan B5	16000 h
Lifespan B50	30000 h

Additional product data

Base (standard designation)	E27	
Mercury content	10.8 mg	
Design / version	Clear	
Product remark	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable	

Capabilities

Dimmable	Yes 1)
Burning position	Any
Enclosed luminaire required	No

¹⁾ In combination with POWERTRONIC PTo

Certificates & Standards

Energy efficiency class	G
-------------------------	---

Energy consumption	77.00 kWh/1000h		
Country-specific categorizations			
ILCOS ST-70-H/E/SL-E27-39/156			
Order reference	NAV-T 70W SUPER		
Order releterice	NAV-1 7000 SUPER		
Energy labelling regulation data acc EU 2019/2015			
Lighting technology used	HPS		
Non-directional or directional	NDLS		
Mains or non-mains	NMLS		
Light source cap-type (or other electric interface)	E27		
Connected light source (CLS)	No		
Color-tuneable light source	No		
Envelope	SECOND		
High luminance light source	No		
Anti-glare shield	No		
Correlated colour temperature type	SINGLE_VALUE		
Claim of equivalent power	No		
Length	155.00 mm		
Height	36,0 mm		
Width	36,0 mm		
Chromaticity coordinate x	0,535		
Chromaticity coordinate y	0,420		
Beam angle correspondence	SPHERE_360		
EPREL ID	546578		
Model number	AC34370,AC34370		

Safety advice

- Disconnect mains before installation.
- Must not be used if outer bulb is defective.
- Protect from spray water.

DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instructions	High Intensity Discharge Lamp UI

	Documents and certificates	Document name	
PDF	Declarations of conformity		
PDF	Certificates	EAC RU C-DE.AYA46.B.85891 29.06.2018-28.06.2023 ROSTEST-Moskva - HPS	
PDF	Certificates	EAC N RU D-DE.MU62.B.00936_20 06.03.2020-05.03.2025 Prommash Test - HPS	
	Photometric and lighting design files	Document name	

ø	٦	
ᆫ	_	

Spectral power distribution

384084_NAV_SUPER_4Y

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899415416	Sleeve 1	39 mm x 39 mm x 196 mm	69.00 g	0.30 dm ³
4052899415423	Shipping box 12	168 mm x 130 mm x 212 mm	980.00 g	4.63 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.