

## PRODUCT DATASHEET

### Emergency Lighting 8 W/640

Basic T5 Short EL | Tubular fluorescent lamps 16 mm, short, for emergency lighting, with G5 base



#### Areas of application

- Public buildings
- Industry
- Shops
- Supermarkets and department stores

#### Product benefits

- Optimized for emergency power operation

#### Product features

- Suitable for emergency power operation




TECHNICAL DATA

Electrical data

|                      |        |
|----------------------|--------|
| Nominal wattage      | 8 W    |
| Construction wattage | 7.50 W |
| Nominal voltage      | 56 V   |
| Nominal current      | 0.15 A |

Photometrical data

|                           |            |
|---------------------------|------------|
| Luminous flux             | 385 lm     |
| Luminous efficacy         | 51 lm/W    |
| Light color (designation) | Cold White |
| Color temperature         | 4000 K     |
| Color rendering index Ra  | ≥60        |
| Light color               | 640        |
| Rated LLMF at 2,000 h     | 0.75       |
| Rated LLMF at 4,000 h     | 0.69       |
| Rated LLMF at 6,000 h     | 0.66       |
| Rated LLMF at 8,000 h     | 0.64       |



349629\_FL\_640

Dimensions & Weight

|                                             |           |
|---------------------------------------------|-----------|
| Overall length                              | 302.50 mm |
| Length with base excl. base pins/connection | 288,00 mm |
| Diameter                                    | 16.00 mm  |
| Tube diameter                               | 16 mm     |
| Product weight                              | 25.71 g   |

Lifespan

|                                       |         |
|---------------------------------------|---------|
| Service life                          | 4500 h  |
| Rated lamp survival factor at 2,000 h | 0.99    |
| Rated lamp survival factor at 4,000 h | 0.99    |
| Rated lamp survival factor at 6,000 h | 0.95    |
| Rated lamp survival factor at 8,000 h | 0.81    |
| Lifespan B50                          | 10000 h |

#### Additional product data

|                             |                                                      |
|-----------------------------|------------------------------------------------------|
| Base (standard designation) | G5                                                   |
| Mercury content             | 2.9 mg                                               |
| Design / version            | Emergency Lighting (Basic) T5 short tubular, G5 base |
| Product remark              | BASIC T5 SHORT for emergency lighting                |

#### Capabilities

|          |     |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

#### Certificates & Standards

|                         |                |
|-------------------------|----------------|
| Energy efficiency class | G              |
| Energy consumption      | 8.00 kWh/1000h |

#### Country-specific categorizations

|                 |                      |
|-----------------|----------------------|
| ILCOS           | FD-8/640-E-G5-16/288 |
| Order reference | L 8W/640 EL          |

#### Energy labelling regulation data acc EU 2019/2015

|                                                     |              |
|-----------------------------------------------------|--------------|
| Lighting technology used                            | OTHER_FL     |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | NMLS         |
| Light source cap-type (or other electric interface) | G5           |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope                                            | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Claim of equivalent power                           | No           |
| Length                                              | 302.50 mm    |

|                           |            |
|---------------------------|------------|
| Height                    | 16.00 mm   |
| Width                     | 16.00 mm   |
| Chromaticity coordinate x | 0,380      |
| Chromaticity coordinate y | 0,394      |
| Beam angle correspondence | SPHERE_360 |
| EPREL ID                  | 546310     |
| Model number              | AC34077    |

### Safety advice

– In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

### DOWNLOAD DATA

| Documents and certificates                                                          |                             | Document name                                                          |
|-------------------------------------------------------------------------------------|-----------------------------|------------------------------------------------------------------------|
|     | Declarations of conformity  | EC Declaration of Conformity - 2021 9C1-4077894-EN-00 - T5 SHORT       |
|    | Certificates                | EAC RU C-DE HA10.B.00671 16 08 2018 15 07 2023 Expert Sertifikaciya FL |
|   | Certificates                | EAC N RU D-DE.MU62.B.00801_20 02.03.2020-01.03.2025 Prommash Test - FL |
| Photometric and lighting design files                                               |                             | Document name                                                          |
|  | Spectral power distribution | 349629_FL_640                                                          |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300606644 | Sleeve<br>1                  | 19 mm x 19 mm x 304 mm               | 36.00 g      | 0.11 dm <sup>3</sup> |
| 4050300606651 | Shipping box<br>25           | 316 mm x 103 mm x 109 mm             | 973.10 g     | 3.55 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

