

# PRODUCT DATASHEET ST 172 SAFETY DEOS

Starters for series operation at 230 V AC (ST 151, ST 172) | Starters for series operation at 230 V AC



#### Product features

- Temperature range for reliable cut-out: -20...+80 °C



## TECHNICAL DATA

#### Electrical data

Nominal wattage	22.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz

## Dimensions & Weight

Diameter	21,5 mm
Product weight	9.39 g

## Additional product data

Mercury content	0.0 mg
Product remark	Temperature range for reliable switch-off: -20+80 °C

## Capabilities

Ī	Dimmable	No

## Country-specific categorizations

Order reference	ST 172/220-240

## Energy labelling regulation data acc EU 2019/2015

Length	40.30 mm
Height	21,5 mm
Width	21.50 mm

#### DOWNLOAD DATA

Documents and certificates		Document name	
PDF	Declarations of conformity	Glow starter for fluorescent lamps	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300854069	Unpacked 1	38 mm x 19 mm x 22 mm	9.39 g	0.02 dm <sup>3</sup>
4050300797786	Tray 25	114 mm x 40 mm x 110 mm	241.75 g	0.50 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300797793	Shipping box 200	227 mm x 98 mm x 227 mm	2086.00 g	5.05 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.