

PRODUCT DATASHEET SPC.T CL 25 W 230 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



Areas of application

- Domestic baking ovens

Product features

- Ambient temperature: up to 300 °C




TECHNICAL DATA

Electrical data

| Nominal wattage | 25 W |
|----------------------|---------|
| Construction wattage | 25.00 W |
| Nominal voltage | 230 V |

Photometrical data

| Luminous flux | 140 lm |
|--------------------------|--------|
| Luminous efficacy | 5 lm/W |
| Color temperature | 2700 K |
| Color rendering index Ra | 100 |
| Light color | 1027 |



349634_HAL_HV_AK

Light technical data

| Starting time | 0 s |
|---------------|-----|
|---------------|-----|

Dimensions & Weight

| Overall length | 55.00 mm |
|---|----------|
| Length with base excl. base pins/connection | 57.00 mm |
| Light center length (LCL) | 45,0 mm |
| Diameter | 26,0 mm |
| Product weight | 7.6 g |

Lifespan

| Lifespan L70/B50 at 25 °C | 1000 h |
|---------------------------|--------|
| | |

Additional product data

| Base (standard designation) | E14 |
|---|---------------------|
| Mercury-free | Yes |
| Capabilities | |
| Dimmable | Yes |
| Certificates & Standards | |
| Energy efficiency class | G |
| Energy consumption | 25.00 kWh/1000h |
| Country-specific categorizations | |
| ILCOS | IBT/C-25-230-E14-26 |
| Order reference | SPC.T26/57 CL 2 |
| Energy labelling regulation data acc EU 2019/2015 | |
| Lighting technology used | OTHER |
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Light source cap-type (or other electric interface) | E14 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 55.00 mm |
| Height | 26,0 mm |
| Width | 26,0 mm |
| Chromaticity coordinate x | 0.487 |
| Chromaticity coordinate y | 0.416 |
| Beam angle correspondence | SPHERE_360 |
| Displacement factor | 1.00 |
| EPREL ID | 714463 |
| | |

AC35307,AC35307

Safety advice

Model number

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.
- Not designed as a replacement for conventional lighting in private household.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|----------|---|---------------------------|
| POF | Declarations of conformity OVEN 15W 25W E14 | |
| | Photometric and lighting design files | Document name |
| <u>~</u> | Spectral power distribution | 349634_HAL_HV_AK |
| | opeotral power distribution | 0+000+_1 // 1L_11V _/ 110 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300774664 | Blister 2 | 29 mm x 140 mm x 120 mm | 29.20 g | 0.49 dm ³ |
| 4050300774671 | Shipping box 20 | 286 mm x 141 mm x 149 mm | 421.00 g | 6.01 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.