

## PRODUCT DATASHEET

### ENDURA Style Cylinder Wall Sensor 6W

ENDURA® STYLE CYLINDER | Stainless steel wall luminaires and bollards with indirect illumination



#### Areas of application

- Outdoor use (IP44)
- Building facades
- Gardens, balconies and other outdoor areas
- Pathway lighting
- Driveways

#### Product benefits

- Energy-efficient thanks to LED technology
- Easy and quick installation
- Long-term energy and cost savings (sensor version)

#### Product features

- Bright and functional outdoor LED luminaires
- Housing made of Polycarbonate covered with stainless steel
- Available as wall, ceiling and bollard luminaires



---

## TECHNICAL DATA

### Electrical data


|                                                             |               |
|-------------------------------------------------------------|---------------|
| Nominal wattage                                             | 6.00 W        |
| Nominal voltage                                             | 220...240 V   |
| Mains frequency                                             | 50...60 Hz    |
| Nominal current                                             | 40.000 mA     |
| Max. number of luminaires per miniature circuit breaker B16 | 320           |
| Max. number of luminaires per miniature circuit breaker C16 | 320           |
| Power factor $\lambda$                                      | > 0.5         |
| Total harmonic distortion                                   | < 120 %       |
| Protection class                                            | II            |
| Operating mode                                              | Mains voltage |

### Photometrical data

|                                              |            |
|----------------------------------------------|------------|
| Luminous flux                                | 360 lm     |
| Luminous efficacy                            | 60 lm/W    |
| Color temperature                            | 3000 K     |
| Light color (designation)                    | Warm White |
| Color rendering index Ra                     | > 80       |
| Standard deviation of color matching         | < 6 sdcn   |
| Photobiological safety group acc. to EN62778 | RG0        |
| UGR                                          | < 25       |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 102,0 mm  |
| Length         | 150.00 mm |
| Width          | 101.00 mm |
| Height         | 137.00 mm |
| Product weight | 480.00 g  |



PG ENDURA STYLE Cylinder Wall  
Sensor MiPRC

Materials & Colors

|                 |                    |
|-----------------|--------------------|
| Product color   | Steel              |
| Housing color   | Steel              |
| Body material   | Stainless steel    |
| Cover material  | Polycarbonate (PC) |
| Mercury content | 0.0 mg             |

Application & Mounting

|                              |                |
|------------------------------|----------------|
| Ambient temperature range    | -20...+40 °C   |
| Temperature range at storage | -20...+85 °C   |
| Type of connection           | Screw terminal |
| Type of protection           | IP44           |
| Dimmable                     | No             |
| Mounting type                | Surface        |
| Application environment      | Outdoor        |
| With light source            | Yes            |
| Replaceable light source     | No             |

Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 40000 h <sup>1)</sup> |
| Number of switching cycles | 15000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Sensor

|                                  |                |
|----------------------------------|----------------|
| Type of sensor                   | Motion / Light |
| Sensor controlled switching time | 2 s...6 min    |
| Detection range of motion sensor | 9 m            |

|                                        |              |
|----------------------------------------|--------------|
| Detection threshold of daylight sensor | 50...2000 lx |
|----------------------------------------|--------------|

### Certificates & Standards

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Standards                                            | CE / UKCA / EAC |
| Luminaire with limited surface temperature, "D sign" | No              |
| Replaceable light source (EPREL)                     | Not replaceable |

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                        |
|------------------------------------------------------------------------------------|----------------------------------------|--------------------------------------|
|  | User instruction / safety instructions | ENDURA STYLE CYLINDER WALL           |
|  | Legal information                      | Safety insert G11219279              |
|  | Declarations of conformity             | CE Declaration Endura Style Cylinder |
|  | Declarations of conformity UKCA        | Fixed LUM                            |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854453267 | Folding box<br>1             | 124 mm x 154 mm x 166 mm             | 652.00 g     | 3.17 dm <sup>3</sup>  |
| 4099854453274 | Shipping box<br>6            | 380 mm x 175 mm x 320 mm             | 3910.00 g    | 21.28 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.