

# PRODUCT DATASHEET

## LED Worklight Tripod 2x20W 4000K

WORKLIGHTS - TRIPOD | Versatile LED worklight with tripod stand



### Areas of application

- Renovation
- Garages
- Basement
- Workshops

### Product benefits

- Foldable for easy storage
- Energy savings of up to 80% compared to halogen lamp worklights
- Semi-frosted, tempered glass cover for uniform illumination

### Product features

- Available with 1 or 2 luminaire heads
- Rotation angle luminaire head: 360°, swiveling: 180°
- Type of protection, luminaire head and housing: IP65, Type of protection, plug: IP44
- Height adjustment of tripod up to 1.8 m total height
- Quick-release fastener for adjustment of luminaire head angle
- Type E/F plug



---

## TECHNICAL DATA

### Electrical data


|   |                               |
|---|-------------------------------|
| Nominal wattage   | 40.00 W                       |
| Nominal voltage   | 220...240 V                   |
| Mains frequency   | 50...60 Hz                    |
| Nominal current   | 184.000 mA                    |
| Inrush current  | 0,1 A                         |
| Max. number of luminaires per miniature circuit breaker C10 | -                             |
| Power factor $\lambda$                                      | > 0.90                        |
| Total harmonic distortion                                   | < 35 %                        |
| Protection class  | I                             |
| Operating mode  | Electronic control gear (ECG) |

### Photometrical data

|  |            |
|--|------------|
| Luminous flux                                  | 3400 lm    |
| Total luminous flux of contained light sources | 2960 lm    |
| Luminous efficacy                              | 85 lm/W    |
| Color temperature                              | 4000 K     |
| Light color (designation)                      | Cool White |
| Color rendering index Ra                       | ≥80        |
| Standard deviation of color matching           | 6 sdcn     |
| Flickering metric (Pst LM)                     | -          |
| Stroboscope effect metric (SVM)                | -          |
| Photobiological safety group acc. to EN62778   | RG1        |
| Photobiological safety group acc. to EN62471   | RG1        |
| Beam angle                                     | 110 °      |

### Dimensions & Weight

|                |            |
|----------------|------------|
| Length         | 780.00 mm  |
| Width          | 680.00 mm  |
| Height         | 1700.00 mm |
| Product weight | 3400.00 g  |
| Cable length   | 2,0 m      |



LED WOKRLIGHT 2x20W TRIPOD

Materials & Colors

|                                 |                |
|---------------------------------|----------------|
| Product color                   | Dark gray      |
| Housing color                   | Dark gray      |
| Body material                   | Aluminum Steel |
| Cover material                  | Glass          |
| Light emitting surface material | Glass          |
| Mercury content                 | 0.0 mg         |

Application & Mounting

|  |                              |
|--|------------------------------|
| Ambient temperature range              | -20...+45 °C                 |
| Temperature range at storage           | -30...+70 °C                 |
| Type of connection                     | Protective contact Plug type |
| Type of protection                     | IP65 <sup>1)</sup>           |
| Protection class IK (shock resistance) | IK06                         |
| Dimmable                               | No                           |
| Mounting type                          | Standing                     |
| Mounting location                      | Floor                        |
| Application environment                | Outdoor                      |
| Adjustable                             | Yes                          |
| With light source                      | Yes                          |
| Replaceable light source               | No                           |

<sup>1)</sup> Luminaire head and housing IP65, plug IP44

Lifespan

|                            |                       |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C  | 25000 h <sup>1)</sup> |
| Number of switching cycles | 15000                 |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

|  |                 |
|--|-----------------|
| Standards  | CE / EAC        |
| Luminaire with limited surface temperature, "D sign" | No              |
| Replaceable light source (EPREL)                     | Not replaceable |



## EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

## Safety advice

- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

## DOWNLOAD DATA

| Documents and certificates   |  | Document name        |
|--|--|----------------------|
|   | User instruction / safety instructions | LED WORKLIGHT TRIPOD |
|  | Declarations of conformity             | LED WORKLIGHT        |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075213913 | Folding box<br>1             | 148 mm x 173 mm x 644 mm             | 3491.00 g    | 16.49 dm <sup>3</sup> |
| 4058075213920 | Shipping box<br>4            | 360 mm x 310 mm x 665 mm             | 14728.00 g   | 74.21 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.